OSHA EMERGENCY STANDARD:

Subject	Industry Position	NIOSH/Advisory Committee Recommendation	Final OSHA Standard
1. Numerical Standard	Five fibers with no automatic reduction to two fibers.	Five fibers with an automatic reduction to two fibers in two years.	Five fibers with an auto reduction to two fibers i four years.
2. Labeling	No label on locked-in asbestos containing products. The words "cancer" or "danger" should not be used on labels.	All asbestos-containing products should be labeled. Label should carry words "cancer" and "danger."	No label on locked-in ash containing products. Word "cancer" and "danger" wil not be used.
3. Monitoring Frequency	Monitoring should be conducted at a frequency necessary to assure compliance with the environmental standards. Management should decide frequency.	NIOSH: Annual monitoring at stations below TWA. Quarterly monitoring at stations above TWA. ADVISORY COMMITTEE: Twice-yearly monitoring at stations below TWA. Monthly monitoring at stations above TWA.	Monitoring every six mont at stations above TWA. Monitoring at other stati at a frequency to assure compliance with environm standards. Management to decide frequency.
4. Protective Clothing	No protective clothing required below 5-10 times TWA.	NIOSH: Protective clothing required in all areas above limit. ADVISORY COMMITTEE: No protective clothing below 10 times TWA.	Protective clothing requi only where peak exposures above limit (10 fibers) occur.
5. Waste Disposal	Only wastes that generate dust in excess of limits should be bagged.	All waste should be bagged.	Only wastes that generate dust in excess of limits must be bagged.

Published by AsbestosClaims.Law
asbestosclaims.law/library/21011/1