5/18/76

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1367

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.
Johns-Manville Corp. & Subsidiaries	303/770-1000 Ext. 2252

ADDRESS (Number, Street, City, State, and ZIP Code)
Greenwood Plaza, Denver, Colorado 80217

CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS
Asphalt saturated asbestos-cement board	Asbestos EBONY
CHEMICAL FAMILY	FORMULA

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Chrysotile Asbestos Fiber	45	*
*See attached copy of Federal Register of 6/7/72		

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H_2O=1)	1.8
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	10
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER	Virtually nil		

APPEARANCE AND ODOR Dark brown sheet - slight asphaltic odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	FLAMMABLE LIMITS	Lel	Uel
Non-flammable			

EXTINGUISHING MEDIA

SPECIAL FIRE FIGHTING PROCEDURES

UNUSUAL FIRE AND EXPLOSION HAZARDS

(Continued on reverse side)

Form OSHA-20
Rev. May 72

Johns-Manville Material Safety Data Sheet for Asbestos EBONY (1976)
ACL Doc 24039 · Page 1 of 2
Published by AsbestosClaims.Law
asbestosclaims.law/library/24039/1

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE
See attached copy of Federal Register of 6/7/72

EFFECTS OF OVEREXPOSURE
Long term exposure to excessive concentrations of asbestos fiber may cause pulmonary disease.

EMERGENCY AND FIRST AID PROCEDURES
Avoid breathing excessive dust when cutting, drilling or sanding.

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATABILITY *(Materials to avoid)*

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Vacuum clean loose dust and chips. If sweeping is necessary, wet loose material.

WASTE DISPOSAL METHOD
Place waste in closed containers for disposal.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)* Use respirators approved by NIOSH for protection against pneumoconiosis producing dusts.

VENTILATION	LOCAL EXHAUST Control dust generated by fabricating operations to within TLV by use of mechanical exhaust ventilation systems	
	MECHANICAL *(General)*	OTHER

PROTECTIVE GLOVES	EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Maintain good housekeeping practices.

OTHER PRECAUTIONS

PAGE (2)
GPO 930-540

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, JOHNS-MANVILLE CORPORATION MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

Form OSHA-20
Rev. May 72

Published by AsbestosClaims.Law
asbestosclaims.law/library/24039/2