Form Approved
Budget Bureau No. 44R-R1
Approval Expires April 30, 1971

Form No. LSB-OOS-4
May 1969

U.S. DEPARTMENT OF LABOR

WAGE AND LABOR STANDARDS ADMINISTRATION
Bureau of Labor Standards

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME: Johns-Manville Corp. & Subsidiaries
EMERGENCY TELEPHONE NO.: 303-770-1000 Ext. 2252
ADDRESS (Number, Street, City, State, and ZIP Code): Greenwood Plaza, Denver, Colorado 80217
CHEMICAL NAME AND SYNONYMS: 2009 Mechanical Packing
TRADE NAME AND SYNONYMS: CT1 Mechanical Packing
CHEM. FAMILY: Chempac
FORMULA:

SECTION II HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS	N/A		BASE METAL	N/A	
CATALYST	"		ALLOYS	"	
VEHICLE	"		METALLIC COATINGS	"	
SOLVENTS	"		FILLER METAL PLUS COATING OR CORE FLUX	"	
ADDITIVES	"		OTHERS	"	
OTHERS	"				

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Chrysotile asbestos fiber (The asbestos fibers are firmly	26	
bound in the product and under normal usage present no		
health hazard. See Federal Register Vol. 37, No. 110		
part 1910.93a, Wednesday, June 7, 1972)		

SECTION III PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H_2O = 1)	2.0
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	N/A
VAPOR DENSITY (AIR = 1)	N/A	EVAPORATION RATE (_____ = 1)	N/A
SOLUBILITY IN WATER	N/A		

APPEARANCE AND ODOR: Square, rope-like coil

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	N/A	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA	N/A			
SPECIAL FIRE FIGHTING PROCEDURES	N/A			
UNUSUAL FIRE AND EXPLOSION HAZARDS	N/A			

PRODUCED
JM - 83

Published by AsbestosClaims.Law
asbestosclaims.law/library/24050/1

SECTION V HEALTH HAZARD DATA

Refer to Section II

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASTE DISPOSAL METHOD

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) Refer to Section II

VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General)	OTHER

PROTECTIVE GLOVES | EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Maximum operating temperature: 500°F

PRODUCED
JM - 83

Published by AsbestosClaims.Law
asbestosclaims.law/library/24050/2