DISCONTINUED PRODUCT

10/22/79

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.
Johns-Manville Corp. & Subsidiaries	303/979-1000 Ext. 3119
ADDRESS (Number, Street, City, State, and ZIP Code) Ken-Caryl Ranch, Denver, Colorado 80217	
CHEMICAL NAME AND SYNONYMS Chrysotile Asbestos Fiber	TRADE NAME AND SYNONYMS FIBROID Asbestos Paper
CHEMICAL FAMILY	FORMULA

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Chrysotile Asbestos Fiber	Approx 95	*
*For TLV see attached Federal Register of 6/7/72		

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H_2O=1)	2.5
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (____ ____ =1)	
SOLUBILITY IN WATER	Slight		
APPEARANCE AND ODOR	Solid material - no odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	FLAMMABLE LIMITS	Lel	Uel
NA			
EXTINGUISHING MEDIA: Non-flammable			
SPECIAL FIRE FIGHTING PROCEDURES			
UNUSUAL FIRE AND EXPLOSION HAZARDS			

(Continued on reverse side)

Johns-Manville Material Safety Data Sheet for FIBROID Asbestos Paper (1979)
ACL Doc 24055 · Page 1 of 2
Published by AsbestosClaims.Law
asbestosclaims.law/library/24055/1

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE
See Section II

EFFECTS OF OVEREXPOSURE
Overexposure to excessive concentrations of asbestos fiber may cause pulmonary disease.

EMERGENCY AND FIRST AID PROCEDURES

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATABILITY *(Materials to avoid)*
None

HAZARDOUS DECOMPOSITION PRODUCTS
None

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Recommend the use of vacuum cleaning to remove scrap and chips generated by fabricating operations.

WASTE DISPOSAL METHOD
Comply with 40 CFR Chapter 1, Part 61

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)*
NIOSH approved for protection against pneumoconiosis-producing dusts.

VENTILATION	LOCAL EXHAUST Recommended at mechanical fabricating operations	SPECIAL
	MECHANICAL *(General)*	OTHER

PROTECTIVE GLOVES	EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Maintain good housekeeping practices.

OTHER PRECAUTIONS

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, JOHNS-MANVILLE CORPORATION MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

Published by AsbestosClaims.Law
asbestosclaims.law/library/24055/2