2/23/78 DISCONTINUED PRODUCT

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.
Johns-Manville Corp.	303/978-3118
ADDRESS (Number, Street, City, State, and ZIP Code) Ken-Caryl Ranch, Denver, Colorado 80217	
CHEMICAL NAME AND SYNONYMS Asbestos-Calcium Silicate Board	TRADE NAME AND SYNONYMS MARINITE 23
CHEMICAL FAMILY	FORMULA

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Amosite Asbestos Fiber by weight approx.	25	*
*See attached (29 CFR 1910.1001)		

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H_2O=1)	0.37
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER			
APPEARANCE AND ODOR	Grey Solid Sheet - No Odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	FLAMMABLE LIMITS	Lel	Uel

EXTINGUISHING MEDIA Non-flammable

SPECIAL FIRE FIGHTING PROCEDURES

UNUSUAL FIRE AND EXPLOSION HAZARDS

(Continued on reverse side)

Form OSHA-20
Rev. May 72

Johns-Manville Material Safety Data Sheet for MARINITE 23 (1978)
ACL Doc 24071 · Page 1 of 2
Published by AsbestosClaims.Law
asbestosclaims.law/library/24071/1

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE
See Section II

EFFECTS OF OVEREXPOSURE
Overexposure to excessive concentrations of asbestos fiber may cause pulmonary disease.

EMERGENCY AND FIRST AID PROCEDURES
Avoid breathing excessive dust during fabricating operations.

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATABILITY *(Materials to avoid)*: None

HAZARDOUS DECOMPOSITION PRODUCTS: None

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Vacuum clean loose dust and chips. If sweeping is necessary, wet loose material.

WASTE DISPOSAL METHOD
Dispose of waste in closed containers.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)*
See attached Federal Register.
NIOSH approved respirator for protection against pneumoconiosis producing dusts.

VENTILATION	LOCAL EXHAUST	Control dust generated by fabricating operations to within TLV by use of mechanical exhaust ventilation systems.
	MECHANICAL *(General)*	
	SPECIAL	
	OTHER	

PROTECTIVE GLOVES

EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Maintain good housekeeping practices. Vacuum clean or wet down waste when cleaning.

OTHER PRECAUTIONS

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, JOHNS-MANVILLE CORPORATION MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.