6/25/79

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.
Johns-Manville Corp. & Subsidiaries	303/979-1000 Ext. 3119
ADDRESS (Number, Street, City, State, and ZIP Code)	
Ken-Caryl Ranch, Denver, Colorado 80217	
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS
Compressed rubber bonded asbestos fiber sheet gasket	Style 60 Service Sheet
CHEMICAL FAMILY	FORMULA

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Chrysotile Asbestos Fiber	Approx 85	*
*For TLV see attached Federal Register of 6/7/72		
Asbestos fibers locked in product by rubber binder.		

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H_2O=1)	1.65
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	< 1
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER	Negligible		
APPEARANCE AND ODOR	Medium gray sheet - slight petroleum solvent odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	NA	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA	NA			
SPECIAL FIRE FIGHTING PROCEDURES				
UNUSUAL FIRE AND EXPLOSION HAZARDS				

PRODUCED
JM - 83

(Continued on reverse side)

Johns-Manville Material Safety Data Sheet for Style 60 Service Sheet (1979)
ACL Doc 24084 · Page 1 of 2
Published by AsbestosClaims.Law
asbestosclaims.law/library/24084/1

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

See Section II

EFFECTS OF OVEREXPOSURE

Overexposure to excessive concentrations of asbestos fiber may cause pulmonary disease.

EMERGENCY AND FIRST AID PROCEDURES

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATABILITY *(Materials to avoid)*

None in designed use.

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF RELEASE MATERIAL IS RELEASED OR SPILLED

NA

WASTE DISPOSAL METHOD

Comply with 40 CFR Chapter 1, Part 61

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)* Normally not required. If necessary use respirators approved by NIOSH for protection against pneumoconiosis producing dusts.

VENTILATION	LOCAL EXHAUST Normally not necessary	SPECIAL
	MECHANICAL *(General)*	OTHER

PROTECTIVE GLOVES | EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Maintain good housekeeping practices.

OTHER PRECAUTIONS

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, JOHNS-MANVILLE CORPORATION MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

Form OSHA-20
May 72

PRODUCED
JM - 03

Published by AsbestosClaims.Law
asbestosclaims.law/library/24084/2