5/31/79

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.
Johns-Manville Corp. & Subsidiaries	303/979-1000 Ext. 3119

ADDRESS (Number, Street, City, State, and ZIP Code)
Ken-Caryl Ranch, Denver, Colorado 80217

CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS
Compressed rubber bonded asbestos fiber sheet gasket	Style 70C Service Sheet
CHEMICAL FAMILY	FORMULA

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Asbestos fiber	75	*
*For TLV see attached Federal Register of 6/7/72		
Asbestos fibers locked in product by rubber binder		

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H_2O=1)	1.65
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	< 1
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____ =1)	
SOLUBILITY IN WATER	Negligible		
APPEARANCE AND ODOR	Gray-black sheet - slight solvent odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)		FLAMMABLE LIMITS	Lel	Uel
	NA			
EXTINGUISHING MEDIA	NA			

SPECIAL FIRE FIGHTING PROCEDURES

UNUSUAL FIRE AND EXPLOSION HAZARDS

PRODUCED
JM - 83

(Continued on reverse side)

Form OSHA-20
Rev. May 72

Johns-Manville Material Safety Data Sheet for Style 70C Service Sheet (1979)
ACL Doc 24086 · Page 1 of 2
Published by AsbestosClaims.Law
asbestosclaims.law/library/24086/1

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II

EFFECTS OF OVEREXPOSURE: Overexposure to excessive concentrations of asbestos fiber may cause pulmonary disease.

EMERGENCY AND FIRST AID PROCEDURES:

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATABILITY *(Materials to avoid)*: None in designed use.

HAZARDOUS DECOMPOSITION PRODUCTS: NA

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: NA

WASTE DISPOSAL METHOD: Comply with 40 CFR Chapter 1, Part 61

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)*: Normally not required. If necessary use respirators approved by NIOSH for protection against pneumoconiosis-producing dusts.

VENTILATION: LOCAL EXHAUST: Normally not necessary. | MECHANICAL *(General)* | SPECIAL | OTHER

PROTECTIVE GLOVES | EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Maintain good housekeeping practices.

OTHER PRECAUTIONS:

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, JOHNS-MANVILLE CORPORATION MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

Form OSHA-20
Rev. May 72

PRODUCED
JM - 83

Published by AsbestosClaims.Law
asbestosclaims.law/library/24086/2