5/31/79

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

SECTION I

MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.
Johns-Manville Corp. & Subsidiaries	303/979-1000 Ext. 3119

ADDRESS (Number, Street, City, State, and ZIP Code)
Ken-Caryl Ranch, Denver, Colorado 80217

CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS
Braided Asbestos Packing	VG-1 Mechanical Packing
CHEMICAL FAMILY	FORMULA

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					

HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES	%	TLV (Units)
Asbestos Fiber	25	*
*For TLV see attached Federal Register of 6/7/72		

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H_2O=1)	
VAPOR PRESSURE (mm Hg.)		PERCENT, VOLATILE BY VOLUME (%)	
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____=1)	
SOLUBILITY IN WATER	Negligible		
APPEARANCE AND ODOR	Braided packing - rectangular cross section		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	FLAMMABLE LIMITS	Lel	Uel
NA			

EXTINGUISHING MEDIA
NA

SPECIAL FIRE FIGHTING PROCEDURES

UNUSUAL FIRE AND EXPLOSION HAZARDS

PRODUCED
JM - 83

(Continued on reverse side)

Form OSHA-20
Rev. May 72

Johns-Manville Material Safety Data Sheet for VG-1 Mechanical Packing (1979)
ACL Doc 24098 · Page 1 of 2
Published by AsbestosClaims.Law
asbestosclaims.law/library/24098/1

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section II

EFFECTS OF OVEREXPOSURE: Overexposure to excessive concentrations of asbestos fiber may cause pulmonary disease.

EMERGENCY AND FIRST AID PROCEDURES:

SECTION VI - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATABILITY *(Materials to avoid)*: None in designed use.

HAZARDOUS DECOMPOSITION PRODUCTS: NA

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: NA

WASTE DISPOSAL METHOD: Comply with 40 CFR Chapter 1, Part 61

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION *(Specify type)*: Normally not required.

VENTILATION	LOCAL EXHAUST: NA	SPECIAL
	MECHANICAL *(General)*	OTHER

PROTECTIVE GLOVES | EYE PROTECTION

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

OTHER PRECAUTIONS

While the information and recommendations set forth herein are believed to be accurate as of the date hereof, JOHNS-MANVILLE CORPORATION MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.

Form OSHA-20
Rev. May 72

PRODUCED
JM - 83

Published by AsbestosClaims.Law
asbestosclaims.law/library/24098/2