PLAINTIFF'S EXHIBIT
UC-1938

WV-0046 #11

ENVIRONMENTAL PROTECTION AGENCY REGULATIONS ON NATIONAL EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS

(40 CFR 61; 38 FR 8820, April 6, 1973; Amended by Code of Federal Regulations, Volume 40, Revised as of July 1, 1975; 40 FR 42195, September 11, 1975; 40 FR 45171, October 1, 1975; 40 FR 48292, October 14, 1975; 40 FR 48347, October 15, 1975; 40 FR 50719, October 31, 1975; 40 FR 58646, December 18, 1975; 40 FR 59729, December 30, 1975; 41 FR 1914, January 13, 1976; 41 FR 4264, January 29, 1976; 41 FR 7750, February 20, 1976; 41 FR 11820, March 22, 1976; 41 FR 19633, May 13, 1976; 41 FR 21450, May 26, 1976; 41 FR 24885, June 21, 1976; 41 FR 27967, July 8, 1976; 41 FR 33264, August 9, 1976; 41 FR 34629, August 16, 1976; 41 FR 36918, September 1, 1976)

Subpart A—General Provisions

§ 61.01 Applicability.

The provisions of this part apply to the owner or operator of any stationary source for which a standard is prescribed under this part.

§ 61.02 Definitions.

As used in this part, all terms not defined herein shall have the meaning given them in the act:

(a) "Act" means the Clean Air Act (42 U.S.C. 1857 et seq.).

(b) "Administrator" means the Administrator of the Environmental Protection Agency or his authorized representative.

(c) "Alternative method" means any method of sampling and analyzing for an air pollutant which is not a reference method or an equivalent method but which has been demonstrated to the Administrator's satisfaction to produce, in specific cases, results adequate for his determination of compliance.

[39 FR 15936, May 3, 1974]

(d) "Commenced" means that an owner or operator has undertaken a continuous program of construction or modification or that an owner or operator has entered into a contractual obligation to undertake and complete, within a reasonable time, a continuous program of construction or modification.

(e) "Compliance schedule" means the date or dates by which a source or category of sources is required to comply with the standards of this part and with any steps toward such compliance which are set forth in a waiver of compliance under § 61.11.

(f) "Construction" means fabrication, erection, or installation of a stationary source.

(g) "Effective date" is the date of promulgation in the FEDERAL REGISTER of an applicable standard or other regulation under this part.

(h) "Equivalent method" means any method of sampling and analyzing for an air pollutant which has been demonstrated to the Administrator's satisfaction to have a consistent and quantitatively known relationship to the reference method, under specified conditions.

(i) "Existing source" means any stationary source which is not a new source.

(j) "Modification" means any physical change in, or change in the method of operation of, a stationary source which increases the amount of any hazardous air pollutant emitted by such source or which results in the emission of any hazardous air pollutant not previously emitted, except that:

(1) Routine maintenance, repair, and replacement shall not be considered physical changes, and

(2) The following shall not be considered a change in the method of operation:

(i) An increase in the production rate, if such increase does not exceed the operating design capacity of the stationary source;

(ii) An increase in hours of operation.

(k) "New source" means any stationary source, the construction or modification of which is commenced after the publication in the FEDERAL REGISTER of proposed national emission standards for hazardous air pollutants which will be applicable to such source.

(l) "Owner or operator" means any person who owns, leases, operates, controls, or supervises a stationary source.

(m) "Reference method" means any method of sampling and analyzing for an air pollutant, as described in appendix B to this part.

(n) "Startup" means the setting in operation of a stationary source for any purpose.

(o) "Standard" means a national emission standard for a hazardous air pollutant proposed or promulgated under this part.

(p) "Stationary source" means any building, structure, facility, or installation which emits or may emit any air pollutant which has been designated as hazardous by the Administrator.

§ 61.03 Abbreviations.

The abbreviations used in this part have the following meanings:

°C—Degrees Centigrade.
cfm—Cubic feet per minute.
ft²—Square feet.
ft³—Cubic feet.
°F—Degrees Fahrenheit.
in—Inch.
l—Liter.
ml—Milliliter.
M—Molar.
m³—Cubic meter.
nm—Nanometer.
oz—Ounces.
v/v—Volume per volume.
yd²—Square yards.
w.g.—Water gage.
inHg—Inches of mercury.
inH₂O—Inches of water.
g—Grams.
mg—Milligrams.
N—Normal.
°R—Degree Rankine.
min—Minute
sec—Second.
avg.—Average.
I.D.—Inside diameter.
O.D.—Outside diameter.
μg—Micrograms (10^{-6} gram).
%—Percent.
Hg—Mercury.
Be—Beryllium.

§ 61.04 Address.

(a) All requests, reports, applications, submittals, and other communications to the Administrator pursuant to this part shall be submitted in duplicate and addressed to the appropriate Regional Office of the Environmental Protection Agency, to the attention of the Director, Enforcement Division. The regional offices are as follows:

Region I (Connecticut, Maine, New Hampshire, Massachusetts, Rhode Island, Vermont), John F. Kennedy Federal Building, Boston, Massachusetts 02203.

Region II (New York, New Jersey, Puerto Rico, Virgin Islands), Federal Office Building, 26 Federal Plaza (Foley Square), New York, N.Y. 10007.

Region III (Delaware, District of Columbia, Pennsylvania, Maryland, Virginia, West Virginia), Curtis Building, Sixth and Walnut Streets, Philadelphia, Pennsylvania 19106.

Region IV (Alabama, Florida, Georgia, Mississippi, Kentucky, North Carolina, South Carolina, Tennessee), Suite 300, 1421 Peachtree Street, Atlanta, Georgia 30309.

Region V (Illinois, Indiana, Minnesota, Michigan, Ohio, Wisconsin), 1 North Wacker Drive, Chicago, Illinois 60606.

Region VI (Arkansas, Louisiana, New Mexico, Oklahoma, Texas), 1600 Patterson Street, Dallas, Texas 75201.

Region VII (Iowa, Kansas, Missouri, Nebraska), 1735 Baltimore Street, Kansas City, Missouri 63108.

Region VIII (Colorado, Montana, North Dakota, South Dakota, Utah, Wyoming), 198 Lincoln Towers, 1860 Lincoln Street, Denver, Colorado 80203.

Region IX (Arizona, California, Hawaii, Nevada, Guam, American Samoa), 100 California Street, San Francisco, California 94111.

Region X (Washington, Oregon, Idaho, Alaska), 1200 Sixth Avenue, Seattle, Washington 98101.

(b) Section 112(d) directs the Administrator to delegate to each State, when appropriate, the authority to implement and enforce the national emission standards for hazardous air pollutants for stationary sources located in such State. All information required to be submitted to EPA under paragraph (a) of this section, must also be submitted to the appropriate State Agency of any State to which this authority has been delegated (provided, that each specific delegation may exempt sources from a certain federal or State reporting requirement). The appropriate mailing address for those States whose delegation request has been approved is as follows:

(A)-(E) [reserved]

(F) California:

Bay Area Pollution Control District, 939 Ellis St., San Francisco, CA 94109

Copyright © 1976 by The Bureau of National Affairs, Inc.

BRG 0484

Union Carbide trial exhibit UC-1938: EPA National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 6... Published by AsbestosClaims.Law
ACL Doc 16996 · Page 1 of 9 asbestosclaims.law/library/16996/1

Del Norte County Air Pollution Control District, Courthouse, Crescent City, CA 95531
Fresno County Air Pollution Control District, 515 S. Cedar Avenue, Fresno, CA 93702
Humboldt County Air Pollution Control District, 5600 S. Broadway, Eureka, CA 95501
Kern County Air Pollution Control District, 1700 Flower St. (P.O. Box 997), Bakersfield, CA 93302
Madera County Air Pollution Control District, 135 W. Yosemite Avenue, Madera, CA 93637
Mendocino County Air Pollution Control District, County Courthouse, Ukiah, CA 95482
Monterey Bay Unified Air Pollution Control District, 420 Church St. (P.O. Box 487), Salinas, CA 93901
Northern Sonoma County Air Pollution Control District, 3312 Chanate Rd., Santa Rosa, CA 95404
Sacramento County Air Pollution Control District, 2221 Stockton Blvd., Sacramento, CA 95827
San Joaquin County Air Pollution Control District, 1601 E. Hazelton St. (P.O. Box 2009), Stockton, CA 95201
Trinity County Air Pollution Control District, Box AJ, Weaverville, CA 96093
Ventura County Air Pollution Control District, 625 E. Santa Clara St., Ventura, CA 93001

[41 FR 45171, October 1, 1975; 41 FR 21450, May 26, 1976; 41 FR 27967, July 8, 1976; 41 FR 33264, August 9, 1976]

(G)—State of Colorado, Colorado Air Pollution Control Division, 4210 East 11th Avenue, Denver, Colorado 80220.

[40 FR 50719, October 31, 1975]

(H) State of Connecticut, Department of Environmental Protection, State Office Building, Hartford, Connecticut 06115.

[41 FR 11920, March 22, 1976]

(I)-(K) [reserved].

(L) State of Georgia, Environmental Protection Division, Department of Natural Resources, 270 Washington Street, S.W., Atlanta, Georgia 30334.

[41 FR 24888, June 21, 1976]

(M)-(T) [reserved].

(U) State of Maine, Department of Environmental Protection, State House, Augusta, Maine 04330.

[40 FR 59739, December 30, 1975]

(V) [reserved]

(W) Massachusetts Department of Environmental Quality Engineering, Division of Air Quality Control, 600 Washington Street, Boston, Massachusetts 02111.

[41 FR 19633 May 13, 1976]

(X) State of Michigan, Air Pollution Control Division, Michigan Department of Natural Resources, Stevens T. Mason Building, 8th Floor, Lansing, Michigan 48926.

[41 FR 1914, January 13, 1976]

(Y)-(DD) [reserved]

(EE) New Hampshire Air Pollution Control Agency, Department of Health and Welfare, State Laboratory Building, Hazen Drive, Concord, New Hampshire 03301.

[41 FR 19633, May 13, 1976]

(FF), (GG) [reserved]

(HH)—New York: New York State Department of Environmental Conservation, 50 Wolf Road, Albany, New York 12233, attention: Division of Air Resources.

[40 FR 48347, October 15, 1975]

(II)-(LL) [reserved]

(MM)—State of Oregon, Department of Environmental Quality, 1234 SW Morrison Street, Portland, Oregon 97205.

[41 FR 7750, February 20, 1976]

(NN)-(UU) [reserved]

(VV) Commonwealth of Virginia, Virginia State Air Pollution Control Board, Room 1106, Ninth Street Office Building, Richmond, Virginia 23219.

[41 FR 8346, February 26, 1976]

(WW) (i) Washington; State of Washington, Department of Ecology, Olympia, Washington 98504.

(ii) Northwest Air Pollution Authority, 207 Pioneer Building, Second and Pine Streets, Mount Vernon, Washington 98273.

(iii) Puget Sound Air Pollution Control Agency, 410 West Harrison Street, Seattle, Washington 98119.

(iv) Spokane County Air Pollution Control Authority, North 811 Jefferson, Spokane, Washington 99201.

(v) Yakima County Clean Air Authority, County Courthouse, Yakima, Washington 98901.

[40 FR 58640, December 18, 1975]

(vi) Olympic Air Pollution Control Authority, 120 East State Avenue, Olympia, Washington 98501.

(vii) Southwest Air Pollution Control Authority, Suite 7601 H, NE Hazel Dell Avenue, Vancouver, Washington 98665.

[41 FR 4264, January 29, 1976]

(XX)-(ZZ) [reserved].

(AAA), (BBB) [reserved].

(CCC)—U.S. Virgin Islands: U.S. Virgin Islands Department of Conservation and Cultural Affairs, P.O. Box 578, Charlotte Amalie, St. Thomas, U.S. Virgin Islands 00801.

[41 FR 34629, August 16, 1976]

(DDD) [reserved].

[39 FR 37987, October 25, 1974; 40 FR 18169, April 25, 1975; 40 FR 42195, September 11, 1975]

§ 61.05 Prohibited activities.

(a) After the effective date of any standard prescribed under this part, no owner or operator shall construct or modify any stationary source subject to such standard without first obtaining written approval of the Administrator in accordance with this subpart, except under an exemption granted by the President under section 112(c)(2) of the act. Sources, the construction or modification of which commenced after the publication date of the standards proposed to be applicable to such source, are subject to this prohibition.

(b) After the effective date of any standard prescribed under this part, no owner or operator shall operate any new source in violation of such standard except under an exemption granted by the President under section 112(c)(2) of the act.

(c) Ninety days after the effective date of any standard prescribed under this part, no owner or operator shall operate any existing stationary source in violation of such standard, except under a waiver granted by the Administrator in accordance with this subpart or under an exemption granted by the President under section 112(c)(2) of the act.

(d) No owner or operator subject to the provisions of this part shall fail to report, revise reports, or report source test results as required under this part.

§ 61.06 Determination of construction or modification.

Upon written application by an owner or operator, the Administrator will make a determination of whether actions taken or intended to be taken by such owner or operator constitute construction or modification or the commencement thereof within the meaning of this part. The Administrator will, within 30 days of receipt of sufficient information to evaluate an application, notify the owner or operator of his determination.

§ 61.07 Application for approval of construction or modification.

(a) The owner or operator of any new source to which a standard prescribed under this part is applicable shall, prior to the date on which construction or modification is planned to commence, or within 30 days after the effective date in the case of a new source that already has commenced construction or modification and has not begun operation, submit to the Administrator an application for approval of such construction or modification. A separate application shall be submitted for each stationary source.

(b) Each application shall include:

(1) The name and address of the applicant.

(2) The location or proposed location of the source.

(3) Technical information describing the proposed nature, size, design, operating design capacity, and method of operation of the source, including a description of any equipment to be used for control of emissions. Such technical information shall include calculations of emission estimates in sufficient detail to permit assessment of the validity of such calculations.

§ 61.08 Approval by Administrator.

(a) The Administrator will, within 60 days of receipt of sufficient information to evaluate an application under § 61.07, notify the owner or operator of approval or intention to deny approval of construction or modification.

(b) If the Administrator determines that a stationary source for which an application pursuant to § 61.07 was submitted will, if properly operated, not cause emissions in violation of a standard, he will approve the construction or modification of such source.

(c) Prior to denying any application for approval of construction or modification pursuant to this section, the Administrator will notify the owner or operator making such application of the Administrator's intention to issue such denial, together with:

(1) Notice of the information and findings on which such intended denial is based, and

(2) Notice of opportunity for such owner or operator to present, within such time limit as the Administrator shall

BRG 0485

Union Carbide trial exhibit UC-1938: EPA National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 6... Published by AsbestosClaims.Law
ACL Doc 16996 · Page 2 of 9 asbestosclaims.law/library/16996/2

specify, additional information or arguments to the Administrator prior to final action on such application.

(d) A final determination to deny any application for approval will be in writing and will set forth the specific grounds on which such denial is based. Such final determination will be made within 60 days of presentation of additional information or arguments, or 60 days after the final date specified for presentation, if no presentation is made.

(e) Neither the submission of an application for approval nor the Administrator's granting of approval to construct or modify shall:

(1) Relieve an owner or operator of legal responsibility for compliance with any applicable provision of this part or of any other applicable Federal, State, or local requirement, or

(2) Prevent the Administrator from implementing or enforcing this part or taking any other action under the act.

§ 61.09 Notification of startup.

(a) Any owner or operator of a source which has an initial startup after the effective date of a standard prescribed under this part shall furnish the Administrator written notification as follows:

(1) A notification of the anticipated date of initial startup of the source not more than 60 days nor less than 30 days prior to such date.

(2) A notification of the actual date of initial startup of the source within 15 days after such date.

§ 61.10 Source reporting and waiver request.

(a) The owner or operator of any existing source, or any new source to which a standard prescribed under this part is applicable which had an initial startup which preceded the effective date of a standard prescribed unde shall, within 90 days after th date, provide the following in in writing to the Administrator

(1) Name and address of or operator.

(2) The location of the sou

(3) The type of hazardous emitted by the stationary sour

(4) A brief description of t size, design, and method of op the stationary source includin erating design capacity of suc Identify each point of emission hazardous pollutant.

(5) The average weight per the hazardous materials being by the source, over the last 1 preceding the date of the repor

(6) A description of the exist trol equipment for each emissio

10-22-76

Copyright © 1976 by The Bureau of National Affair

Published by AsbestosClaims.Law
asbestosclaims.law/library/16996/3

(i) Primary control device(s) for each hazardous pollutant.

(ii) Secondary control device(s) for each hazardous pollutant.

(iii) Estimated control efficiency (percent) for each control device.

(7) A statement by the owner or operator of the source as to whether he can comply with the standards prescribed in this part within 90 days of the effective date.

(b) The owner or operator of an existing source unable to operate in compliance with any standard prescribed under this part may request a waiver of compliance with such standard for a period not exceeding 2 years from the effective date. Any request shall be in writing and shall include the following information:

(1) A description of the controls to be installed to comply with the standard.

(2) A compliance schedule, including the date each step toward compliance will be reached. Such list shall include as a minimum the following dates:

(i) Date by which contracts for emission control systems or process modifications will be awarded, or date by which orders will be issued for the purchase of component parts to accomplish emission control or process modification;

(ii) Date of initiation of onsite construction or installation of emission control equipment or process change;

(iii) Date by which onsite construction or installation of emission control equipment or process modification is to be completed; and

(iv) Date by which final compliance is to be achieved.

(3) A description of interim emission control steps which will be taken during the waiver period.

(4) Changes in the information provided under paragraph (a) of this section shall be provided to the Administrator within 30 days after such change, except that if changes will result from modification of the source, as defined in § 61.02 (j), the provisions of § 61.07 and § 61.08 are applicable.

(d) The format for reporting under this section is included as appendix A of this part. Advice on reporting the status of compliance may be obtained from the Administrator.

§ 61.11 Waiver of compliance.

(a) Based on the information provided in any request under § 61.10, or other information, the Administrator may grant a waiver of compliance with a standard for a period not exceeding 2 years from the effective date of such standard.

(b) Such waiver will be in writing and will:

(1) Identify the stationary source covered.

(2) Specify the termination date of the waiver. The waiver may be terminated at an earlier date if the conditions specified under paragraph (b) (3) of this section are not met.

(3) Specify dates by which steps toward compliance are to be taken; and impose such additional conditions as the Administrator determines to be necessary to assure installation of the necessary controls within the waiver period, and to assure protection of the health of persons during the waiver period.

(c) Prior to denying any request for a waiver pursuant to this section, the Administrator will notify the owner or operator making such request of the Administrator's intention to issue such denial, together with:

(1) Notice of the information and findings on which such intended denial is based, and

(2) Notice of opportunity for such owner or operator to present, within such time limit as the Administrator specifies, additional information or arguments to the Administrator prior to final action on such request.

(d) A final determination to deny any request for a waiver will be in writing and will set forth the specific grounds on which such denial is based. Such final determination will be made within 60 days after presentation of additional information or arguments, or 60 days after the final date specified for such presentation, if no presentation is made.

(e) The granting of a waiver under this section shall not abrogate the Administrator's authority under section 114 of the act.

§ 61.12 Emission tests and monitoring.

(a) Emission tests and monitoring shall be conducted and reported as set forth in this part and appendix B to this part.

(b) The owner or operator of a new source subject to this part, and at the request of the Administrator, the owner or operator of an existing source subject to this part, shall provide or cause to be provided, emission testing facilities as follows:

(1) Sampling ports adequate for test methods applicable to such source.

(2) Safe sampling platform(s).

(3) Safe access to sampling platform(s).

(4) Utilities for sampling and testing equipment.

§ 61.13 Waiver of emission tests.

(a) Emission tests may be waived upon written application to the Administrator if, in his judgment, the source is meeting the standard, or if the source is operating under a waiver of compliance or has requested a waiver of compliance.

(b) If application for waiver of the emission test is made, such application shall accompany the information required by § 61.10. The appropriate form is contained in appendix A to this part.

(c) Approval of any waiver granted pursuant to this section shall not abrogate the Administrator's authority under the act or in any way prohibit the Administrator from later canceling such waiver. Such cancellation will be made only after notice is given to the owner or operator of the source.

§ 61.14 Source test and analytical methods.

(a) Methods 101, 102, and 104 in appendix B to this part shall be used for all source tests required under this part, unless an equivalent method or an alternative method has been approved by the Administrator.

(b) Method 103 in appendix B to this part is hereby approved by the Administrator as an alternative method for sources subject to § 61.32(a) and § 61.42 (b).

(c) The Administrator may, after notice to the owner or operator, withdraw approval of an alternative method granted under paragraphs (a), (b) or (d) of this section. Where the test results using an alternative method do not adequately indicate whether a source is in compliance with a standard, the Administrator may require the use of the reference method or its equivalent.

(d) Method 105 in Appendix B to this part is hereby approved by the Administrator as an alternative method for sources subject to § 61.52(b).

[40 FR 48292, October 14, 1975]

§ 61.15 Availability of information.

The availability to the public of information provided to, or otherwise obtained by, the Administrator under this part shall be governed by Part 2 of this chapter.

[41 FR 36918, September 1, 1976]

§ 61.16 State authority.

(a) The provisions of this part shall not be construed in any manner to preclude any State or political subdivision thereof from:

(1) Adopting and enforcing any emission limiting regulation applicable to a stationary source, provided that such emission limiting regulation is not less stringent than the standards prescribed under this part.

(2) Requiring the owner or operator of a stationary source, other than a stationary source owned or operated by the United States, to obtain permits, licenses, or approvals prior to initiating construction, modification, or operation of such source.

§ 61.17 Circumvention.

No owner or operator subject to the provisions of this part shall build, erect, install, or use any article, machine, equipment, process, or method, the use of which conceals an emission which would

Copyright © 1976 by The Bureau of National Affairs, Inc.

Union Carbide trial exhibit UC-1938: EPA National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 6...

Published by AsbestosClaims.Law

ACL Doc 16996 · Page 4 of 9

asbestosclaims.law/library/16996/4

otherwise constitute a violation of an applicable standard. Such concealment includes, but is not limited to, the use of gaseous diluents to achieve compliance with a visible emissions standard, and the piecemeal carrying out of an operation to avoid coverage by a standard that applies only to operations larger than a specified size.

[40 FR 48292, October 14, 1975]

Subpart B—National Emission Standard for Asbestos

§ 61.20 Applicability.

The provisions of this subpart are applicable to those sources specified in § 61.22.

§ 61.21 Definitions.

Terms used in this subpart are defined in the act, in subpart A of this part, or in this section as follows:

(a) "Asbestos" means actinolite, amosite, anthophyllite, chrysotile, crocidolite, tremolite.

(b) "Asbestos material" means asbestos or any material containing asbestos.

(c) "Particulate asbestos material" means finely divided particles of asbestos material.

(d) "Asbestos tailings" means any solid waste product of asbestos mining or milling operations which contains asbestos.

(e) "Outside air" means the air outside buildings and structures.

(f) "Visible emissions" means any emissions which are visually detectable without the aid of instruments and which contain particulate asbestos material.

(g) "Asbestos mill" means any facility engaged in the conversion or any intermediate step in the conversion of asbestos ore to commercial asbestos. Outside storage of asbestos materials is not considered a part of such facility.

(h) "Commercial asbestos" means any variety of asbestos which is produced by extracting asbestos from asbestos ore.

(i) "Manufacturing" means the combining of commercial asbestos, or in the case of woven friction products the combining of textiles containing commercial asbestos, with any other material(s), including commercial asbestos, and the processing of this combination into a product as specified in § 61.22(c).

(j) "Demolition" means the wrecking or taking out of any load-supporting structural member and any related removing or stripping of friable asbestos materials.

(k) "Friable asbestos material" means any material that contains more than 1 percent asbestos by weight and that can be crumbled, pulverized, or reduced to powder, when dry, by hand pressure.

(l) "Control device asbestos waste" means any asbestos-containing waste material that is collected in a pollution control device.

(m) "Renovation" means the removing or stripping of friable asbestos material used to insulate or fireproof any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member. Operations in which load-supporting structural members are wrecked or taken out are excluded.

(n) "Planned renovation" means a renovation operation, or a number of such operations, in which the amount of friable asbestos material that will be removed or stripped within a given period of time can be predicted. Operations that are individually non-scheduled are included, provided a number of such operations can be predicted to occur during a given period of time based on operating experience.

(o) "Emergency renovation" means a renovation operation that results from a sudden, unexpected event, and is not a planned renovation. Operations necessitated by non-routine failures of equipment are included.

(p) "Adequately wetted" means sufficiently mixed or coated with water or an aqueous solution to prevent dust emissions.

(q) "Removing" means taking out friable asbestos materials used to insulate or fireproof any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member from any building, structure, facility, or installation.

(r) "Stripping" means taking off friable asbestos materials used for insulation or fireproofing from any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member.

(s) "Fabricating" means any processing of a manufactured product containing commercial asbestos, with the exception of processing at temporary sites for the construction or restoration of buildings, structures, facilities or installations.

(t) "Inactive waste disposal site" means any disposal site or portion thereof where additional asbestos-containing waste material will not be deposited and where the surface is not disturbed by vehicular traffic.

(u) "Active waste disposal site" means any disposal site other than an inactive site.

(v) "Roadways" means surfaces on which motor vehicles travel including, but not limited to, highways, roads, streets, parking areas, and driveways.

(w) "Asbestos-containing waste material" means any waste which contains commercial asbestos and is generated by a source subject to the provisions of this subpart, including asbestos mill tailings, control device asbestos waste, friable asbestos waste material, and bags or containers that previously contained commercial asbestos.

[40 FR 48292, October 14, 1975]

§ 61.22 Emission standard.

(a) Asbestos mills: There shall be no visible emissions to the outside air from any asbestos mill except as provided in paragraph (f) of this section.

[39 FR 15936, May 3, 1974]

(b) Roadways: The surfacing of roadways with asbestos tailings or with asbestos-containing waste that is generated by any source subject to paragraphs (c), (d), (e) or (h), of this section is prohibited, except for temporary roadways on an area of asbestos ore deposits. The deposition of asbestos tailings or asbestos-containing waste on roadways covered with snow or ice is considered "surfacing."

(c) Manufacturing: There shall be no visible emissions to the outside air, except as provided in paragraph (f) of this section, from any of the following operations if they use commercial asbestos or from any building or structure in which such operations are conducted.

[40 FR 48292, October 14, 1975]

(1) The manufacture of cloth, cord, wicks, tubing, tape, twine, rope, thread, yarn, roving, lap, or other textile materials.

(2) The manufacture of cement products.

(3) The manufacture of fireproofing and insulating materials.

(4) The manufacture of friction products.

(5) The manufacture of paper, millboard, and felt.

(6) The manufacture of floor tile.

(7) The manufacture of paints, coatings, caulks, adhesives, sealants.

(8) The manufacture of plastics and rubber materials.

(9) The manufacture of chlorine.

(10) The manufacture of shotgun shells.

(11) The manufacture of asphalt concrete.

(d) Demolition and renovation: The requirements of this paragraph shall apply to any owner or operator of a demolition or renovation operation who intends to demolish any institutional, commercial, or industrial building (including apartment buildings having more than four dwelling units), structure, facility, installation, or portion thereof which contains any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member that is insulated or fireproofed with friable asbestos material, except as provided in paragraph (d) (1) of this section; or who intends to renovate any institutional, commercial, or industrial building, structure, facility, installation, or portion thereof where more than 80 meters (ca. 260 feet) of pipe insulated or fireproofed with friable asbestos material are stripped or removed, or more than 15 square meters (ca. 160 square feet) of friable asbestos material used to insulate or fireproof any duct, boiler, tank, reactor, turbine, furnace, or structural member are stripped or removed.

(1) (i) The owner or operator of a demolition operation is exempted from the requirements of this paragraph provided, (1) the amount of friable asbestos material in the building or portion thereof to be demolished is less than 80 meters (ca. 260 feet) used to insulate pipes, and less than 15 square meters (ca. 160 square feet) used to insulate or fireproof any duct, boiler, tank, reactor, turbine, furnace, or structural member, and (2) the notification requirements of paragraph (d) (1) (ii) are met.

(ii) Written notification shall be postmarked or delivered to the Administrator at least 20 days prior to commencement of demolition and shall include the information required by paragraph (d) (2)

Union Carbide trial exhibit UC-1938: EPA National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 6… Published by AsbestosClaims.Law
ACL Doc 16996 · Page 5 of 9 asbestosclaims.law/library/16996/5

of this section, with the exception of the information required by paragraphs (d)(2)(iii), (vi), (vii), (viii), and (ix), and shall state the measured or estimated amount of friable asbestos material used for insulation and fireproofing which is present. Techniques of estimation shall be explained.

(2) Written notice of intention to demolish or renovate shall be provided to the Administrator by the owner or operator of the demolition or renovation operation. Such notice shall be postmarked or delivered to the Administrator at least 10 days prior to commencement of demolition, or as early as possible prior to commencement of emergency demolition subject to paragraph (d)(6) of this section, and as early as possible prior to commencement of renovation. Such notice shall include the following information:

(i) Name of owner or operator.

(ii) Address of owner or operator.

(iii) Description of the building, structure, facility, or installation to be demolished or renovated, including the size, age, and prior use of the structure, and the approximate amount of friable asbestos material used for insulation and fireproofing.

(iv) Address or location of the building, structure, facility, or installation.

(v) Scheduled starting and completion dates of demolition or renovation.

(vi) Nature of planned demolition or renovation and method(s) to be employed.

(vii) Procedures to be employed to meet the requirements of this paragraph and paragraph (f) of this section.

(viii) The name and address or location of the waste disposal site where the friable asbestos waste will be deposited.

(ix) Name, title, and authority of the State or local governmental representative who has ordered a demolition which is subject to paragraph (d)(6) of this section.

(3)(i) For purposes of determining whether a planned renovating operation constitutes a renovation within the meaning of this paragraph, the amount of friable asbestos material to be removed or stripped shall be:

(A) For planned renovating operations involving individually non-scheduled operations, the additive amount of friable asbestos material that can be predicted will be removed or stripped at a source over the maximum period of time for which a prediction can be made. The period shall be not less than 30 days and not longer than one year.

(B) For each planned renovating operation not covered by paragraph (d)(3)(i)(A), the total amount of friable asbestos material that can be predicted will be removed or stripped at a source.

(ii) For purposes of determining whether an emergency renovating operation constitutes a renovation within the meaning of this paragraph, the amount of friable asbestos material to be removed or stripped shall be the total amount of friable asbestos material that will be removed or stripped as a result of the sudden, unexpected event that necessitated the renovation.

(4) The following procedures shall be used to prevent emissions of particulate asbestos material to outside air:

(i) Friable asbestos materials, used to insulate or fireproof any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member, shall be removed from any building, structure, facility, or installation subject to this paragraph. Such removal shall occur before wrecking or dismantling of any portion of such building, structure, facility, or installation that would break up the friable asbestos materials and before wrecking or dismantling of any other portion of such building, structure, facility, or installation that would preclude access to such materials for subsequent removal. Removal of friable asbestos materials used for insulation or fireproofing of any pipe, duct, or structural member which are encased in concrete or other similar structural material is not required prior to demolition, but such material shall be adequately wetted whenever exposed during demolition.

(ii) Friable asbestos materials used to insulate or fireproof pipes, ducts, boilers, tanks, reactors, turbines, furnaces, or structural members shall be adequately wetted during stripping, except as provided in paragraphs (d)(4)(iv), (d)(4)(vi) or (d)(4)(vii) of this section.

(iii) Pipes, ducts, boilers, tanks, reactors, turbines, furnaces, or structural members that are insulated or fireproofed with friable asbestos materials may be taken out of any building, structure, facility, or installation subject to this paragraph as units or in sections provided the friable asbestos materials exposed during cutting or disjointing are adequately wetted during the cutting or disjointing operation. Such units shall not be dropped or thrown to the ground, but shall be carefully lowered to ground level.

(iv) The stripping of friable asbestos materials used to insulate or fireproof any pipe, duct, boiler, tank, reactor, turbine, furnace, or structural member that has been removed as a unit or in sections as provided in paragraph (d)(4)(iii) of this section shall be performed in accordance with paragraph (d)(4)(ii) of this section. Rather than comply with the wetting requirement, a local exhaust ventilation and collection system may be used to prevent emissions to the outside air. Such local exhaust ventilation systems shall be designed and operated to capture the asbestos particulate matter produced by the stripping of friable asbestos material. There shall be no visible emissions to the outside air from such local exhaust ventilation and collection systems except as provided in paragraph (f) of this section.

(v) All friable asbestos materials that have been removed or stripped shall be adequately wetted to ensure that such materials remain wet during all remaining stages of demolition or renovation and related handling operations. Such materials shall not be dropped or thrown to the ground or a lower floor. Such materials that have been removed or stripped more than 50 feet above ground level, except those materials removed as units or in sections, shall be transported to the ground via dust-tight chutes or containers.

(vi) Except as specified below, the wetting requirements of this paragraph are suspended when the temperature at the point of wetting is below 0°C (32°F). When friable asbestos materials are not wetted due to freezing temperatures, such materials on pipes, ducts, boilers, tanks, reactors, turbines, furnaces, or structural members shall, to the maximum extent possible, be removed as units or in sections prior to wrecking. In no case shall the requirements of paragraphs (d)(4)(iv) or (d)(4)(v) be suspended due to freezing temperatures.

(vii) For renovation operations, local exhaust ventilation and collection systems may be used, instead of wetting as specified in paragraph (d)(4)(ii), to prevent emissions of particulate asbestos material to outside air when damage to equipment resulting from the wetting would be unavoidable. Upon request and supply of adequate information, the Administrator will determine whether damage to equipment resulting from wetting to comply with the provisions of this paragraph would be unavoidable. Such local exhaust ventilation systems shall be designed and operated to capture the asbestos particulate matter produced by the stripping and removal of friable asbestos material. There shall be no visible emissions to the outside air from such local exhaust ventilation and collection systems, except as provided in paragraph (f) of this section.

(5) Sources subject to this paragraph are exempt from the requirements of §§ 61.05(a), 61.07, and 61.09.

(6) The demolition of a building, structure, facility, or installation, pursuant to an order of an authorized representative of a State or local governmental agency, issued because that building is structurally unsound and in danger of imminent collapse is exempt from all but the following requirements of paragraph (d) of this section:

(i) The notification requirements specified by paragraph (d)(2) of this section;

(ii) The requirements on stripping of friable asbestos materials from previously removed units or sections as specified in paragraph (d)(4)(iv) of this section;

(iii) The wetting, as specified by paragraph (d)(4)(v) of this section, of friable asbestos materials that have been removed or stripped;

(iv) The portion of the structure being demolished that contains friable asbestos materials shall be adequately wetted during the wrecking operation.

[39 FR 15936, May 3, 1974; 40 FR 48292, October 14, 1975]

(e) Spraying: There shall be no visible emissions to the outside air from the spray-on application of materials containing more than 1 percent asbestos, on a dry weight basis, used to insulate or fireproof equipment and machinery, except as provided in paragraph (f) of this section. Spray-on materials used to insulate or fireproof buildings, structures, pipes, and conduits shall contain less

Copyright © 1976 by The Bureau of National Affairs, Inc.

BRG 0489

Union Carbide trial exhibit UC-1938: EPA National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 6... Published by AsbestosClaims.Law
ACL Doc 16996 · Page 6 of 9 asbestosclaims.law/library/16996/6

than 1 percent asbestos on a dry weight basis.

(1) Sources subject to this paragraph are exempt from the requirements of § 61.05(a), § 61.07, and § 61.09.

(2) Any owner or operator who intends to spray asbestos materials which contain more than 1 percent asbestos on a dry weight basis to insulate or fireproof equipment and machinery shall report such intention to the Administrator at least 20 days prior to the commencement of the spraying operation. Such report shall include the following information:

[40 FR 48293, October 14, 1975]

(i) Name of owner or operator.

(ii) Address of owner or operator.

(iii) Location of spraying operation.

(iv) Procedures to be followed to meet the requirements of this paragraph.

(f) Rather than meet the no-visible-emission requirements as specified by paragraphs (a), (c), (d), (e), (h), (j), and (k) of this section, an owner or operator may elect to use the methods specified by § 61.23 to clean emissions containing particulate asbestos material before such emissions escape to, or are vented to, the outside air.

(g) Where the presence of uncombined water is the sole reason for failure to meet the no-visible-emission requirement of paragraphs (a), (c), (d), (e), (h), (j), or (k) of this section, such failure shall not be a violation of such emission requirements.

(h) Fabricating: There shall be no visible emissions to the outside air, except as provided in paragraph (f) of this section, from any of the following operations if they use commercial asbestos or from any building or structure in which such operations are conducted.

(1) The fabrication of cement building products.

(2) The fabrication of friction products, except those operations that primarily install asbestos friction materials on motor vehicles.

(3) The fabrication of cement or silicate board for ventilation hoods; ovens; electrical panels; laboratory furniture; bulkheads, partitions and ceilings for marine construction; and flow control devices for the molten metal industry.

(i) Insulating: Molded insulating materials which are friable and wet-applied insulating materials which are friable after drying, installed after the effective date of these regulations, shall contain no commercial asbestos. The provisions of this paragraph do not apply to insulating materials which are spray applied; such materials are regulated under § 61.22(e).

(j) Waste disposal for manufacturing, fabricating, demolition, renovation and spraying operations: The owner or operator of any source covered under the provisions of paragraphs (c), (d), (e), or (h) of this section shall meet the following standards:

(1) There shall be no visible emissions to the outside air, except as provided in paragraph (j)(3) of this section, during the collection; processing, including incineration; packaging; transporting; or deposition of any asbestos-containing waste material which is generated by such source.

(2) All asbestos-containing waste material shall be deposited at waste disposal sites which are operated in accordance with the provisions of § 61.25.

(3) Rather than meet the requirement of paragraph (j)(1) of this section, an owner or operator may elect to use either of the disposal methods specified under (j)(3)(i) and (ii) of this section, or an alternative disposal method which has received prior approval by the Administrator:

(i) Treatment of asbestos-containing waste material with water:

(A) Control device asbestos waste shall be thoroughly mixed with water into a slurry and other asbestos-containing waste material shall be adequately wetted. There shall be no visible emissions to the outside air from the collection, mixing and wetting operations, except as provided in paragraph (f) of this section.

(B) After wetting, all asbestos-containing waste material shall be sealed into leak-tight containers while wet, and such containers shall be deposited at waste disposal sites which are operated in accordance with the provisions of § 61.25.

(C) The containers specified under paragraph (j)(3)(i)(B) of this section shall be labeled with a warning label that states:

CAUTION

Contains Asbestos
Avoid Opening or Breaking Container
Breathing Asbestos is Hazardous to Your Health

Alternatively, warning labels specified by Occupational Safety and Health Standards of the Department of Labor, Occupational Safety and Health Administration (OSHA) under 29 CFR 1910.-93a(g)(2)(ii) may be used.

(ii) Processing of asbestos-containing waste material into non-friable forms:

(A) All asbestos-containing waste material shall be formed into non-friable pellets or other shapes and deposited at waste disposal sites which are operated in accordance with the provisions of § 61.25.

(B) There shall be no visible emissions to the outside air from the collection and processing of asbestos-containing waste material, except as specified in paragraph (f) of this section.

(4) For the purposes of this paragraph (j), the term all asbestos-containing waste material as applied to demolition and renovation operations covered by paragraph (d) of this section includes only friable asbestos waste and control device asbestos waste.

(k) Waste disposal for asbestos mills: The owner or operator of any source covered under the provisions of paragraph (a) of this section shall meet the following standard:

(1) There shall be no visible emissions to the outside air, except as provided in paragraph (k)(3) of this section, during the collection, processing, packaging, transporting or deposition of any asbestos-containing waste material which is generated by such source.

(2) All asbestos-containing waste material shall be deposited at waste disposal sites which are operated in accordance with the provisions of § 61.25.

(3) Rather than meet the requirement of paragraph (k)(1) of this section, an owner or operator may elect to meet the following requirements in paragraphs (k)(3)(i) and (ii), or use an alternative disposal method which has received prior approval by the Administrator:

(i) There shall be no visible emissions to the outside air from the transfer of control device asbestos waste to the tailings bank except as provided in paragraph (f) of this section. Such waste shall be subsequently processed either as specified in paragraph (k)(3)(ii) of this section or as specified in paragraph (j)(3) of this section.

(ii) All asbestos-containing waste material shall be adequately mixed, with a wetting agent recommended by the manufacturer of the agent to effectively wet dust and tailings, prior to deposition at a waste disposal site. Such agent shall be used as recommended for the particular dust by the manufacturer of the agent. There shall be no discharge of visible emissions to the outside air from the wetting operation except as specified in paragraph (f) of this section. Wetting may be suspended when the ambient temperature at the waste disposal site is less than −9.5°C (ca. 15°F). The ambient air temperature shall be determined by an appropriate measurement method with an accuracy of ±1°C (±2°F) and recorded at least at hourly intervals during the period that the operation of the wetting system is suspended. Records of such temperature measurements shall be retained at the source for a minimum of two years and made available for inspection by the Administrator.

(l) The owner of any inactive waste disposal site, which was operated by sources covered under § 61.22 (a), (c) or (h) and where asbestos-containing waste material produced by such sources was deposited, shall meet the following standards:

(1) There shall be no visible emissions to the outside air from an inactive waste disposal site subject to this paragraph, except as provided in paragraph (l)(5) of this section.

(2) Warning signs shall be displayed at all entrances, and along the property line of the site or along the perimeter of the sections of the site where asbestos-containing waste material was deposited, at intervals of 100 m (ca. 330 ft) or less, except as specified in paragraph (l)(4) of this section. Signs shall be posted in such a manner and location that a person may easily read the legend. The warning signs required by this paragraph shall conform to the requirements of 20" x 14" upright format signs specified in 29 CFR 1910.145(d)(4) and this paragraph. The signs shall display the following legend in the lower panel, with letter sizes and styles of a visibility at least equal to those specified in this paragraph.

BRG 0490

Union Carbide trial exhibit UC-1938: EPA National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 6... Published by AsbestosClaims.Law
ACL Doc 16996 · Page 7 of 9 asbestosclaims.law/library/16996/7

LEGEND

ASBESTOS WASTE DISPOSAL SITE

DO NOT CREATE DUST

BREATHING ASBESTOS IS HAZARDOUS TO YOUR HEALTH

Notation

1" Sans Serif, Gothic or Block

¾" Sans Serif, Gothic or Block

14 Point Gothic

Spacing between lines shall be at least equal to the height of the upper of the two lines.

(3) The perimeter of the site shall be fenced in a manner adequate to deter access by the general public, except as specified in paragraph (3)(ii) of this section.

(4) Warning signs and fencing are not required where the requirements of paragraphs (3)(i), (ii), or (iii) of this section are met, or where a natural barrier adequately deters access by the general public. Upon request and supply of appropriate information, the Administrator will determine whether a fence or a natural barrier adequately deters access to the general public.

(5) Rather than meet the requirement of paragraph (3)(i) of this section, an owner may elect to meet the requirements of this paragraph or may use an alternative control method for emissions from inactive waste disposal sites which has received prior approval by the Administrator.

(i) The asbestos-containing waste material shall be covered with at least 15 centimeters (ca. 6 inches) of compacted non-asbestos-containing material, and a cover of vegetation shall be grown and maintained on the area adequate to prevent exposure of the asbestos-containing waste material; or

(ii) The asbestos-containing waste material shall be covered with at least 60 centimeters (ca. 2 feet) of compacted non-asbestos-containing material and maintained to prevent exposure of the asbestos-containing waste; or

(iii) For inactive waste disposal sites for asbestos tailings, a resinous or petroleum-based dust suppression agent which effectively binds dust and controls wind erosion shall be applied. Such agent shall be used as recommended for the particular asbestos tailings by the dust suppression agent manufacturer. Other equally effective dust suppression agents may be used upon prior approval by the Administrator. For purposes of this paragraph, waste crankcase oil is not considered a dust suppression agent.

[40 FR 48292, October 14, 1975]

§ 61.23 Air-cleaning.

If air-cleaning is elected, as permitted by §§ 61.22(f) and 61.22(d)(4)(iv), the requirements of this section must be met.

[40 FR 48292, October 14, 1975]

(a) Fabric filter collection devices must be used, except as noted in paragraphs (b) and (c) of this section. Such devices must be operated at a pressure drop of no more than 4 inches water gage, as measured across the filter fabric. The airflow permeability, as determined by ASTM method D737-69, must not exceed 30 ft³/min/ft² for woven fabrics or 35 ft³/min/ft² for felted fabrics, except that 40 ft³/min/ft² for woven and 45 ft³/min/ft² for felted fabrics is allowed for filtering air from asbestos ore dryers. Each square yard of felted fabric must weigh at least 14 ounces and be at least one-sixteenth inch thick throughout. Synthetic fabrics must not contain fill yarn other than that which is spun.

(b) If the use of fabric filters creates a fire or explosion hazard, the administrator may authorize the use of wet collectors designed to operate with a unit contacting energy of at least 40 inches water gage pressure.

(c) The administrator may authorize the use of filtering equipment other than that described in paragraphs (a) and (b) of this section if the owner or operator demonstrates to the satisfaction of the administrator that the filtering of particulate asbestos material is equivalent to that of the described equipment.

(d) All air-cleaning equipment authorized by this section must be properly installed, used, operated, and maintained. Bypass devices may be used only during upset or emergency conditions and then only for so long as it takes to shut down the operation generating the particulate asbestos material.

§ 61.24 Reporting.

The owner or operator of any existing source to which this subpart is applicable shall, within 90 days after the effective date, provide the following information to the administrator:

(a) A description of the emission control equipment used for each process;

(b) If a fabric filter device is used to control emissions, the pressure drop across the fabric filter in inches water gage.

(1) If the fabric filter device utilizes a woven fabric, the airflow permeability in ft³/min/ft²; and, if the fabric is synthetic, indicate whether the fill yarn is spun or not spun.

(2) If the fabric filter device utilizes a felted fabric, the density in oz/yd², the minimum thickness in inches, and the airflow permeability in ft³/min/ft².

(c) For sources subject to §§ 61.22(j) and 61.22(k):

(1) A brief description of each process that generates asbestos-containing waste material.

(2) The average weight of asbestos-containing waste material disposed of, measured in kg/day.

(3) The emission control methods used in all stages of waste disposal.

(4) The type of disposal site or incineration site used for ultimate disposal, the name of the site operator, and the name and location of the disposal site.

(d) For sources subject to § 61.22(l):

(1) A brief description of the site.

(2) The method or methods used to comply with the standard, or alternative procedures to be used.

(e) Such information shall accompany the information required by § 61.10. The information described in this section shall be reported using the format of Appendix A of this part.

[40 FR 48292, October 14, 1975]

§ 61.25 Waste disposal sites.

In order to be an acceptable site for disposal of asbestos-containing waste material under § 61.22 (j) and (k), an active waste disposal site shall meet the requirements of this section.

(a) There shall be no visible emissions to the outside air from any active waste disposal site where asbestos-containing waste material has been deposited, except as provided in paragraph (e) of this section.

(b) Warning signs shall be displayed at all entrances, and along the property lines of the site or along the perimeter of the sections of the site where asbestos-containing waste material is deposited, at intervals of 100 m (ca. 330 ft) or less except as specified in paragraph (d) of this section. Signs shall be posted in such a manner and location that a person may easily read the legend. The warning signs required by this paragraph shall conform to the requirements of 20" x 14" upright format signs specified in 29 CFR 1910.145(d)(4) and this paragraph. The signs shall display the following legend in the lower panel, with letter sizes and styles of a visibility at least equal to those specified in this paragraph.

LEGEND

ASBESTOS WASTE DISPOSAL SITE

DO NOT CREATE DUST

BREATHING ASBESTOS IS HAZARDOUS TO YOUR HEALTH

Notation

1" Sans Serif, Gothic or Block

¾" Sans Serif, Gothic or Block

14 Point Gothic

Spacing between lines shall be at least equal to the height of the upper of the two lines.

(c) The perimeter of the disposal site shall be fenced in order to adequately deter access to the general public except as specified in paragraph (d) of this section.

(d) Warning signs and fencing are not required where the requirements of paragraph (e)(1) of this section are met, or where a natural barrier adequately deters access to the general public. Upon request and supply of appropriate information, the Administrator will determine whether a fence or a natural barrier adequately deters access to the general public.

(e) Rather than meet the requirement of paragraph (a) of this section, an owner or operator may elect to meet the requirements of paragraph (e)(1) or (e)(2) of this section, or may use an alternative control method for emissions from active waste disposal sites which has received prior approval by the Administrator.

(1) At the end of each operating day, or at least once every 24-hour period while the site is in continuous operation, the asbestos-containing waste material which was deposited at the site during the operating day or previous 24-hour period shall be covered with at least 15 centimeters (ca. 6 inches) of compacted non-asbestos-containing material.

Copyright © 1976 by The Bureau of National Affairs, Inc.

BRG 0491

Union Carbide trial exhibit UC-1938: EPA National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 6... Published by AsbestosClaims.Law
ACL Doc 16996 · Page 8 of 9 asbestosclaims.law/library/16996/8

(2) At the end of each operating day, or at least once every 24-hour period while the disposal site is in continuous operation, the asbestos-containing waste material which was deposited at the site during the operating day or previous 24-hour period shall be covered with a resinous or petroleum-based dust suppression agent which effectively binds dust and controls wind erosion. Such agent shall be used as recommended for the particular dust by the dust suppression agent manufacturer. Other equally effective dust suppression agents may be used upon prior approval by the Administrator. For purposes of this paragraph, waste crankcase oil is not considered a dust suppression agent.

[40 FR 48292, October 14, 1975]

Subpart C—National Emission Standard for Beryllium

§ 61.30 Applicability.

The provisions of this subpart are applicable to the following stationary sources:

(a) Extraction plants, ceramic plants, foundries, incinerators, and propellant plants which process beryllium ore, beryllium, beryllium oxide, beryllium alloys, or beryllium-containing waste.

(b) Machine shops which process beryllium, beryllium oxides, or any alloy when such alloy contains more than 5 percent beryllium by weight.

§ 61.31 Definitions.

Terms used in this subpart are defined in the act, in subpart A of this part, or in this section as follows:

(a) "Beryllium" means the element beryllium. Where weights or concentrations are specified, such weights or concentrations apply to beryllium only, excluding the weight or concentration of any associated elements.

(b) "Extraction plant" means a facility chemically processing beryllium ore to beryllium metal, alloy, or oxide, or performing any of the intermediate steps in these processes.

(c) "Beryllium ore" means any naturally occurring material mined or gathered for its beryllium content.

(d) "Machine shop" means a facility performing cutting, grinding, turning, honing, milling, deburring, lapping, electrochemical machining, etching, or other similar operations.

(e) "Ceramic plant" means a manufacturing plant producing ceramic items.

(f) "Foundry" means a facility engaged in the melting or casting of beryllium metal or alloy.

(g) "Beryllium-containing waste" means material contaminated with beryllium and/or beryllium compounds used or generated during any process or operation performed by a source subject to this subpart.

(h) "Incinerator" means any furnace used in the process of burning waste for the primary purpose of reducing the volume of the waste by removing combustible matter.

(i) "Propellant" means a fuel and oxidizer physically or chemically combined which undergoes combustion to provide rocket propulsion.

(j) "Beryllium alloy" means any metal to which beryllium has been added in order to increase its beryllium content and which contains more than 0.1 percent beryllium by weight.

(k) "Propellant plant" means any facility engaged in the mixing, casting, or machining of propellant.

§ 61.32 Emission standard.

(a) Emissions to the atmosphere from stationary sources subject to the provisions of this subpart shall not exceed 10 grams of beryllium over a 24-hour period, except as provided in paragraph (b) of this section.

(b) Rather than meet the requirement of paragraph (a) of this section, an owner or operator may request approval from the Administrator to meet an ambient concentration limit on beryllium in the vicinity of the stationary source of 0.01 $\mu g/m^3$, averaged over a 30-day period.

(1) Approval of such requests may be granted by the Administrator provided that:

(i) At least 3 years of data is available which in the judgment of the Administrator demonstrates that the future ambient concentrations of beryllium in the vicinity of the stationary source will not exceed 0.01 $\mu g/m^3$, averaged over a 30-day period. Such 3-year period shall be the 3 years ending 30 days before the effective date of this standard.

(ii) The owner or operator requests such approval in writing within 30 days after the effective date of this standard.

(iii) The owner or operator submits a report to the Administrator within 45 days after the effective date of this standard which report includes the following information:

(a) Description of sampling method including the method and frequency of calibration.

(b) Method of sample analysis.

(c) Averaging technique for determining 30-day average concentrations.

(d) Number, identity, and location (address, coordinates, or distance and heading from plant) of sampling sites.

(e) Ground elevations and height above ground of sampling inlets.

(f) Plant and sampling area plots showing emission points and sampling sites. Topographic features significantly affecting dispersion including plant building heights and locations shall be included.

(g) Information necessary for estimating dispersion including stack height, inside diameter, exit gas temperature, exit velocity or flow rate, and beryllium concentration.

(h) A description of data and procedures (methods or models) used to design the air sampling network (i.e., number and location of sampling sites).

(i) Air sampling data indicating beryllium concentrations in the vicinity of the stationary source for the 3-year period specified in paragraph (b)(1) of this section. This data shall be presented chronologically and include the beryllium concentration and location of each individual sample taken by the network and the corresponding 30-day average beryllium concentrations.

(2) Within 60 days after receiving such report, the Administrator will notify the owner or operator in writing whether approval is granted or denied. Prior to denying approval to comply with the provisions of paragraph (b) of this section, the Administrator will consult with representatives of the stationary source for which the demonstration report was submitted.

(c) The burning of beryllium and/or beryllium-containing waste, except propellants, is prohibited except in incinerators, emissions from which must comply with the standard.

§ 61.33 Stack sampling.

(a) Unless a waiver of emission testing is obtained under § 61.13, each owner or operator required to comply with § 61.32(a) shall test emissions from his source.

(1) Within 90 days of the effective date in the case of an existing source or a new source which has an initial startup date preceding the effective date; or

(2) Within 90 days of startup in the case of a new source which did not have an initial startup date preceding the effective date.

(b) The Administrator shall be notified at least 30 days prior to an emission test so that he may at his option observe the test.

(c) Samples shall be taken over such a period or periods as are necessary to accurately determine the maximum emissions which will occur in any 24-hour period. Where emissions depend upon the relative frequency of operation of different types of processes, operating hours, operating capacities, or other factors, the calculation of maximum 24-hour-period emissions will be based on that combination of factors which is likely to occur during the subject period and which result in the maximum emissions. No changes in the operation shall be made, which would potentially increase emissions above that determined by the most recent source test, until a new emission level has been estimated by calculation and the results reported to the Administrator.

(d) All samples shall be analyzed and beryllium emissions shall be determined within 30 days after the source test. All determinations shall be reported to the Administrator by a registered letter dispatched before the close of the next business day following such determination.

(e) Records of emission test results and other data needed to determine total emissions shall be retained at the source and made available, for inspection by the Administrator, for a minimum of 2 years.

§ 61.34 Air sampling.

(a) Stationary sources subject to § 61.32(b) shall locate air sampling sites in accordance with a plan approved by the Administrator. Such sites shall be located in such a manner as is calculated to detect maximum concentrations of beryllium in the ambient air.

(b) All monitoring sites shall be operated continuously except for a reasonable time allowance for instrument maintenance and calibration, for changing

BRG 0492

Union Carbide trial exhibit UC-1938: EPA National Emission Standards for Hazardous Air Pollutants, 40 CFR Part 6... Published by AsbestosClaims.Law
ACL Doc 16996 · Page 9 of 9 asbestosclaims.law/library/16996/9