WV-0228 #30

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS, AND RELATED MATERIALS
REPLACES NPCA 1-82

MANUFACTURER'S NAME Plastic Coatings Corp.
P.O. Box 1068 St. Albans, WV 25177
DATE OF PREPARATION
11/22/85

EMERGENCY TELEPHONE NO.
304-755-9151
INFORMATION TELEPHONE NO.
304-~~755-9151~~

SECTION I — PRODUCT IDENTIFICATION

PRODUCT NUMBER 600 & 601
PRODUCT NAME JAXSAN
PRODUCT CLASS Latex Weatherbarrier/Mastic

SECTION II — HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT WT	OCCUPATIONAL EXPOSURE LIMITS TLV	PEL	VAPOR PRESSURE
Chrysotile Asbestos (CAS # 1332-21-4)	4.32%	TLV (C) 10 fibers longer than 5 micrometers per cubic centimeter of air		
Chlorinated Parrafin (CAS # 63449-39-8)	5%	Not listed ACGIH		

SECTION III — PHYSICAL DATA

BOILING RANGE 212°F.
EVAPORATION RATE ☐ FASTER
VAPOR DENSITY > 1
SLOWER ☒ THAN ETHER
☒ HEAVIER
% VOLATILE VOLUME 50%
☐ LIGHTER THAN AIR
WT/GAL 10.95/11.32 Will vary with viscosity.

PLAINTIFF'S EXHIBIT
UC-2067

UCC 019829

Union Carbide trial exhibit UC-2067: Plastic Coatings Corp. Material Safety Data Sheet for JAXSAN 600 & 601 Late... Published by AsbestosClaims.Law
ACL Doc 17089 · Page 1 of 1 asbestosclaims.law/library/17089/1