45085 JAXSON 600 WV-0191 #157

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS, AND RELATED MATERIALS
REPLACES NPCA 1-82

MANUFACTURER'S NAME Plastic Coatings Corp.
P.O. Box 1068 St. Albans, WV 25177
DATE OF PREPARATION
11/22/85

EMERGENCY TELEPHONE NO.
304-755-9151
INFORMATION TELEPHONE NO.
304-755-9151

SECTION I — PRODUCT IDENTIFICATION

PRODUCT NUMBER 600 & 601
PRODUCT NAME JAXSAN
PRODUCT CLASS Latex Weatherbarrier/Mastic

SECTION II — HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT WT	OCCUPATIONAL EXPOSURE LIMITS TLV	PEL	VAPOR PRESSURE
Chrysotile Asbestos * (CAS # 1332-21-4)	4.32%	TLV (C) 10 fibers longer than 5 micrometers per cubic centimeter of air		
Chlorinated Parrafin (CAS # 63449-39-8)	5%	Not listed ACGIH		

RECEIVED
APR 30 1986
MSDS CONTROL

* THE ASBESTOS IN JAXSAN PRODUCTS IS ENCAPSULATED IN A RESINOUS BINDER AND THEREBY RENDERED NON-HAZARDOUS.

SECTION III — PHYSICAL DATA

BOILING RANGE 212°F.
EVAPORATION RATE ☐ FASTER
SLOWER ☒ THAN ETHER
VAPOR DENSITY > 1
☒ HEAVIER
% VOLATILE VOLUME 50%
☐ LIGHTER THAN AIR
WT/GAL 10.95/11.32 Will vary with viscosity.

HEALTH	0
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B

PLAINTIFF'S EXHIBIT
UC-2292

UCC 002272

Published by AsbestosClaims.Law
asbestosclaims.law/library/17284/1

SECTION IV — FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION Non-flammable wet — OSHA Class III B — DOT _____ — FLASH POINT N/A — LEL N/A

EXTINGUISHING MEDIA:

☒ FOAM ☐ "ALCOHOL" FOAM ☒ CO2 ☒ DRY CHEMICAL ☒ WATER FOG ☐ OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS Closed containers may explode when exposed to extreme heat.

SPECIAL FIREFIGHTING PROCEDURES Use full protective firefighting equipment, including self-contained breathing aparatus.

Water may be used to cool closed containers to prevent pressure build-up.

SECTION V — HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE No health hazards are known.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Minor skin irritation is possible upon repeated contact .

PRIMARY ROUTE(S) OF ENTRY: ☒ DERMAL ☒ INHALATION ☒ INGESTION

EMERGENCY AND FIRST AID PROCEDURES DERMAL: Remove material with soap and water. Remove contaminated clothing.
EYES: Flush with large amounts of clean water for at least 15 minutes. Consult physican for medical treatment.
INHALATION: Remove to fresh air. INGESTION: Drink 1-2 glasses of water to dilute. Do not induce vomiting. Consult physican or poison control center immediately. Treat symptomatically.

SECTION VI — REACTIVITY DATA

STABILITY ☐ UNSTABLE ☒ STABLE

HAZARDOUS POLYMERIZATION ☐ MAY OCCUR ☒ WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS
CO, CO_2, HCL

CONDITIONS TO AVOID

INCOMPATIBILITY (MATERIALS TO AVOID)
WET - Materials reactive to water, may cause a chemical reaction.

DRY - Does not react.

UCC 002273

SECTION VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED - Clean and or dilute with water. Clean spills with soap and water.

WASTE DISPOSAL METHOD - Dispose of in accordance with local, state, federal regulations pertaining to non-hazardous latex type wastes.

SECTION VIII — SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION - Use approved mechanical filter respirator to remove solid airborne particles of overspray during spray application.

VENTILATION - No special measures of ventilation needed.

PROTECTIVE GLOVES - None required but recommend water resistant type.
EYE PROTECTION - Wear safety goggles when spraying.

OTHER PROTECTIVE EQUIPMENT - None known
HYGIENIC PRACTICES: Do not allow prolonged contact with skin. Wash with soap and water after contact and before eating.

SECTION IX — SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Damaged by freezing. Store above 32°F. (0°C)

OTHER PRECAUTIONS - Do not take internally.
Avoid eye contact.

PREPARED BY J. G. WIDDECOMBE

UCC 002274

Published by AsbestosClaims.Law
asbestosclaims.law/library/17284/3