SUBJECT: Handling, installing, removing and/or disposing of material containing asbestos.

1.0 PURPOSE:

1.1 To provide a safe procedure for the handling of material containing asbestos. Asbestos is defined to include Chrysotile, Amosite, Crocidolite, Tremolite, Anthophyllite, and Actinolite.

2.0 INTRODUCTION:

2.1 Excessive exposure to asbestos fiber is harmful to your health. These fibers have been associated with cancer of the lungs, throat, stomach, colon, and rectum. The maximum permissible exposure is two (2) fibers, longer than five (5) micrometers, per cubic centimeter of air when averaged over 8 hours. At no point in time may an employee be exposed to greater than 10 fibers per cubic centimeter of air.

2.2 Asbestos fiber can be found in insulation used on piping, equipment, etc., that was installed earlier than about 1973 or 1974. This was when the Sistersville Plant deleted asbestos containing insulation from Stores and went to an "asbestos free" insulation.

2.3 Asbestos fibers can also be found in some brake linings used on automobiles, trucks and our work vehicles.

2.4 Asbestos fibers can also be found in the wall coverings, insulation, etc., used in the construction industry on older buildings.

3.0 RESPONSIBILITY:

3.1 It is the responsibility of the appropriate first line supervisor and craftspersons to control the safe removal and disposal of asbestos-containing material.

3.2 Based on size, complexity and location, the Safety and Health Department shall be notified prior to the start of the job. At that time a decision will be made as to the need for and extent of any monitoring. It is the responsibility of the Supervisor of the personnel handling the asbestos-containing material and the actual individual to request monitoring.

3.3 Proper Housekeeping is the responsibility of each individual in performance of the work assignment. Appropriate equipment for prevention of dust release and clean-up after the job has been provided. Please use this equipment but never use a broom, brush or blow with air when handling materials containing asbestos.

Responsible for review and update of this procedure - Mtce. Dept.

PLAINTIFF'S EXHIBIT
UC-3259

Union Carbide trial exhibit UC-3259: Safety and Health Procedures Manual Section II-15: Handling, Installing, Rem... Published by AsbestosClaims.Law
ACL Doc 18060 · Page 1 of 4 asbestosclaims.law/library/18060/1

3.4 It is the responsibility of the Environmental Protection Control Staff to notify the EPA of the annual amount of asbestos activity in the plant.

3.4.1 The EPA must also be notified prior to large scale jobs. These are defined as stripping of more than 260 linear feet of pipe insulation or more than 160 square feet. It is the responsibility of the Insulator Supervisor to notify the EPC Staff prior to such jobs.

3.5 The responsible supervisor shall ensure that employees using asbestos-containing material have received proper training on the hazards of asbestos.

3.6 If an employee must wear respiratory protection, it is the responsibility of the supervisor to assure that the employee is medically approved and has received proper training on the use of respiratory protection.

3.7 It is the responsibility of the individual craftsperson to wear respiratory equipment when required.

4.0 PROCEDURE:

4.1 All asbestos-containing material will be handled with extreme care and our goal is to take appropriate measures to eliminate all airborne asbestos fibers.

4.2 When asbestos is involved, barricade tape will be used to isolate the area and caution signs will be posted at all access routes to the work area. These signs will be located at a distance which allows an employee to take the necessary protective steps before entering the area. This sign will comply with OSHA specifications and shall read:

ASBESTOS DUST HAZARD

AVOID BREATHING DUST

WEAR ASSIGNED PROTECTIVE EQUIPMENT

DO NOT REMAIN IN AREA UNLESS YOUR WORK REQUIRES IT

BREATHING ASBESTOS DUST MAY BE HAZARDOUS TO YOUR HEALTH

4.3 Asbestos-containing material will be handled, mixed, applied, removed, cut, or otherwise worked on in a wet state sufficient to prevent the emission of airborne asbestos fibers in excess of exposure limits.

Union Carbide trial exhibit UC-3259: Safety and Health Procedures Manual Section II-15: Handling, Installing, Rem... Published by AsbestosClaims.Law
ACL Doc 18060 · Page 2 of 4 asbestosclaims.law/library/18060/2

4.4 Asbestos-containing cement, mortar, coatings, plaster, wrappings, or other materials will not be removed from bags, boxes, or other containers, in which it was shipped, without first wetting, enclosing or ventilating.

4.5 Employees engaged in the handling or removal of asbestos-containing material will wear approved respiratory protection. The individuals will normally be insulators, insulator helpers, and vehicle mechanics. This respiratory protection is mandatory at this location for all exposures to asbestos-containing material. Two types of protection are possible.

4.5.1 Normal Exposure: This is where the concentration of asbestos fibers is reasonably expected to be less than 10 times the permissible exposure limit. In this case, use the Comfo II respirator with the Type H Ultra Filter.

4.5.2 Heavy Exposure: This occurs when the concentration of asbestos is reasonably expected to exceed 100 times the permissible exposure limit. In this situation, a type "C" supplied air respirator in the positive-pressure mode shall be used along with a full facepiece mask.

4.6 Wetting of asbestos-containing material will be done in such a manner as not to wash the fibers into the ground, drainage trenches or sewer facilities. Any fibers contacting the ground will be gathered up and disposed of in approved containers.

4.7 Special wetting agents for asbestos-containing material are available in the Sistersville Plant Store Room. This material is designed to bind the asbestos fibers and reduce or eliminate the potential of dust generation. This wetting material will be used where practical.

4.8 A special Vacuum Cleaner is available, with a special filter designed for 99.97% efficiency. This vacuum cleaner will be used where wetting is not appropriate, such as brake lining work, inside of structures, etc., and for removal of any asbestos-containing material on one's clothing.

4.9 Disposable Protective Clothing designed for exposure to asbestos-containing material will be used on all jobs involving the handling or removal of material containing asbestos.

4.9.1 Disposable Protective Clothing will be worn prior to contact with asbestos-containing material.

4.9.2 Disposable Protective Clothing will be removed at the work site and placed in approved containers.

4.9.3 Protective Clothing will be removed prior to coming in contact with other personnel, eating, smoking or using facilities used by other personnel.

Union Carbide trial exhibit UC-3259: Safety and Health Procedures Manual Section II-15: Handling, Installing, Rem... Published by AsbestosClaims.Law
ACL Doc 18060 · Page 3 of 4 asbestosclaims.law/library/18060/3

4.9.4 New Protective Clothing will be worn for each job or continuation of the job if the previously used Protective Clothing was removed.

4.10 Asbestos-containing material, including used disposable protective clothing, will be collected in impermeable, sealed bags or containers that are labelled according to Paragraph 4.12.

4.10.1 Within the shift that the job is completed, the craftsman or whoever collected the waste material will deliver the bags or containers to the asbestos waste area.

4.10.2 The appropriate supervisor will then notify the Contractor (Charlie Brown) within the same shift that asbestos waste has been delivered for burial.

4.10.3 The Contractor will bury the waste in compliance with federal regulations within 24 hours of being notified.

4.11 Contaminated clothing will be collected and transported in sealed impermeable bags or closed containers, properly labelled as described in Paragraph 4.12. This clothing will be sent to a commercial laundry which has facilities for handling asbestos contaminated clothing.

4.12 Disposal Containers or Laundry Bags shall read:

- Caution -

Contains Asbestos Fibers
Avoid Breathing Dust
Breathing Asbestos Dust
May Cause Serious Bodily Harm

4.13 When an employee has clothing (other than disposable type) contaminated or suspected to be contaminated with asbestos, the employee will:

4.13.1 Enter the "dirty room"-facility provided for insulators and remove clothing.

4.13.2 Contaminated clothing will be placed in sealed containers and sent to laundry.

4.13.3 Enter the shower facility to wash off all asbestos fibers.

4.13.4 The employee will next enter the "clean room" facility and put on clean/uncontaminated clothing.

Union Carbide trial exhibit UC-3259: Safety and Health Procedures Manual Section II-15: Handling, Installing, Rem... Published by AsbestosClaims.Law
ACL Doc 18060 · Page 4 of 4 asbestosclaims.law/library/18060/4