AIRBORNE DUST COUNTS

for

Georgia-Pacific Corporation
Marietta, Ga.

December 8, 1972

Personnel Present: H. Scharf
Georgia-Pacific Corporation

E. J. Kleber
Union Carbide Corporation

J. E. Walsh
Union Carbide Corporation

PLAINTIFF'S EXHIBIT

UC-4993

UNION CARBIDE CORPORATION
Mining and Metals Division
Niagara Falls, New York

SGP 000656

Description of Plant and Tests

Tests were conducted October 30, 1972 at Georgia-Pacific Corp., Marietta, Ga., manufacturers of tape joint compounds.

Asbestos is added at a hopper which has an overhead, negative pressure hood. Personal samples were collected from both the man dumping asbestos and his assistant, handing him the bags. A personal sample was also obtained during the dumping of mica. An environmental sample was placed near the dumping area and allowed to run for approximately one hour.

Sampling and dust counting were carried out in accordance with OSHA Regulation 1910.93a, using the Bayer, Zummalde and Brown method for counting asbestos fibers by phase contrast microscopy (Bureau of Occupational Safety and Health, Feb. 196

Battery powered air pumps (M.S.A. type) calibrated to liters per minute were us to collect personal breathing zone and environmental samples on millipore membrar filters of 0.8 micron porosity.

Fiber counting was performed on a Leitz microscope utilizing phase contrast illum tion at 400X and a Patterson Globe and Circle reticle.

Total dust was determined by light field microscopy at 100X.

Test Results

Two figures have been reported for each sample. They are:

1) Total Fiber - Any material 5 microns or longer having an aspect ratio of 3 or greater. Reported as fibers per milliliter.

2) Total Dust - Any fiber or particle present. Reported as million particles per cubic foot.

Interpretation

The regulations have been established with the 5 fiber limit on a time-weighted average. This essentially means the figures must be arranged to show an employee average intake of fibers per milliliter on an 8-hour day. For example, the highe reading in the test was 8.0 fibers/ml. If this was the only contact with asbest that day, the 2-minute sample would be extrapolated to 8 hours, giving a time-wei average of less than 0.04 fibers/ml.

SGP 00065

SUMMARY OF DUST COUNTS

N.B. No.	Description	Fiber Count Fibers/ml. > 5 μ	m
1929-48-1	Environmental (81 min.) - "Background" sample near filler bins on ladder 15 ft. from bag hopper for small raw material ingredients.	1.7	
1929-48-2	Personal (2 min.) - Operator's assistant handing bags to man who dumps.	6.2	(
1929-48-3	Personal (2 min.) - Operator dumping 2 bags 7RF9 and 3 bags SG-210	8.0	1(
1929-48-4	Personal (2 min.) - Operator dumping 7 bags Muscovite mica	3.6	1:

SGP 000656

AIRBORNE DUST COUNTS

for

Georgia-Pacific Corporation
Marietta, Ga.

December 8, 1972

Personnel Present:

H. Scharf
Georgia-Pacific Corporation

E. J. Kleber
Union Carbide Corporation

J. E. Walsh
Union Carbide Corporation

UNION CARBIDE CORPORATION
Mining and Metals Division
Niagara Falls, New York

SCP 000657

Description of Plant and Tests

Tests were conducted October 30, 1972 at Georgia-Pacific Corp., Marietta, Ga., manufacturers of tape joint compounds.

Asbestos is added at a hopper which has an overhead, negative pressure hood. Personal samples were collected from both the man dumping asbestos and his assistant, handing him the bags. A personal sample was also obtained during the dumping of mica. An environmental sample was placed near the dumping area and allowed to run for approximately one hour.

Sampling and dust counting were carried out in accordance with OSHA Regulation 1910.93a, using the Bayer, Zummalde and Brown method for counting asbestos fibers by phase contrast microscopy (Bureau of Occupational Safety and Health, Feb. 1969

Battery powered air pumps (M.S.A. type) calibrated to 2 liters per minute were us to collect personal breathing zone and environmental samples on millipore membran filters of 0.8 micron porosity.

Fiber counting was performed on a Leitz microscope utilizing phase contrast illum tion at 400X and a Patterson Globe and Circle reticle.

Total dust was determined by light field microscopy at 100X.

Test Results

Two figures have been reported for each sample. They are:

1) Total Fiber - Any material 5 microns or longer having an aspect ratio of 3 or greater. Reported as fibers per milliliter.

2) Total Dust - Any fiber or particle present. Reported as million particles per cubic foot.

Interpretation

The regulations have been established with the 5 fiber limit on a time-weighted average. This essentially means the figures must be arranged to show an employee average intake of fibers per milliliter on an 8-hour day. For example, the highe reading in the test was 8.0 fibers/ml. If this was the only contact with asbest that day, the 2-minute sample would be extrapolated to 8 hours, giving a time-wei average of less than 0.04 fibers/ml.

SGP 000657

SUMMARY OF DUST COUNTS

N.B. No.	Description	Fiber Count Fibers/ml. > 5 μ	T D mm
1929-48-1	Environmental (81 min.) - "Background" sample near filler bins on ladder 15 ft. from bag hopper for small raw material ingredients.	1.7	
1929-48-2	Personal (2 min.) - Operator's assistant handing bags to man who dumps.	6.2	6.
1929-48-3	Personal (2 min.) - Operator dumping 2 bags 7RF9 and 3 bags SG-210	8.0	10.
1929-48-4	Personal (2 min.) - Operator dumping 7 bags Muscovite mica	3.6	13.

SGP 000657