R. E. Byrne, Jr.
J. F. Collins
G. L. Dickson

E. J. Kreber
J. L. Myers
T. P. Norris
W. C. Thurber

E. W. Shortridge
J. E. Walsh
File

UNION CARBIDE

Calidria ASBESTOS

UNION CARBIDE CORPORATION · METALS DIVISION · P. O. BOX 579 · NIAGARA FALLS, N.Y. 14302 · TEL: 716-278-3376

October 24, 1977

PLAINTIFF'S EXHIBIT
UC-5206

Dear "Calidria" Asbestos Customer:

As part of our continuing effort to emphasize the importance of keeping you, your employees and your customers advised of the best practices for using asbestos safely, we are enclosing herewith a copy of our Material Safety Data Sheet for "Calidria" Asbestos, dated September 1, 1976. Additional copies are available from this office upon request.

We are also enclosing a copy of a number of pamphlets published by the Asbestos Information Association/North America (AIA/NA) as follows: "What You Should Know About Asbestos and Health", "Recommended Practices for Handling Asbestos Fiber", "Asbestos in Water" and "Asbestos in the Atmosphere". Also enclosed is a listing of other published material available from AIA/NA. Copies of AIA/NA material may be obtained directly from AIA/NA.

Please advise each of your employees who handles our "Calidria" asbestos that you have such safety data and pamphlets and that they are available to them. In addition, we are also concerned that your customers and ultimately their employees be kept informed by you of the best safety practices for using your products containing asbestos.

We would also like to express our appreciation for your business. Please let me know if we can serve you better in any way.

Very truly yours,

R. E. Byrne, Jr.
Assistant Marketing Manager

REB:dal
Enclosures

DEPOSITION EXHIBIT
AA
MYERS
5/17-09
PENGAD-Bayonne, N.J.

547

Published by AsbestosClaims.Law
asbestosclaims.law/library/19689/1

Material Safety Data

September 1, 1976

UNION CARBIDE CORPORATION • 4625 ROYAL AVENUE • NIAGARA FALLS, NEW YORK • 14302

TELEPHONE: (716) 278-3376

PRODUCT: Chrysotile Asbestos CHEMICAL FORMULA: $Mg_6(OH)_8Si_4O_{10}$

TRADE NAMES: "Calidria" Asbestos

I. PHYSICAL DATA

BOILING POINT AND MELTING POINT: Not Pertinent

SPECIFIC GRAVITY ($H_2O = 1$): 2.45

VOLATILE CONTENT: Absorbed Water 1 – 4% By Weight. Structural Water Approximately 13% by Weight.

APPEARANCE: Pellets or Fine White Powder. No odor. Very Slight Solubility in Water.

II. HAZARDOUS INGREDIENTS

Asbestos contains no hazardous ingredients. However, the material itself can be hazardous under certain conditions. (See V below.)

III. FIRE AND EXPLOSION HAZARD DATA

NON-COMBUSTIBLE MATERIAL: No Fire or Explosion Hazard.

IV. REACTIVITY DATA

INERT MATERIAL: No Decomposition or Polymerization Conditions.

V. HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE TO AIRBORNE CONCENTRATION:

The current Occupational Safety and Health Standard (CFR 29, 1910.1001) contains the following exposure limits:

"The 8-hour time-weighted average airborne concentrations of asbestos fibers to which any employee may be exposed shall not exceed 2 fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the membrane filter method at 400-450 X magnification (4 millimeter objective) phase contrast illumination. No employee shall be exposed at any time to airborne concentrations of asbestos fibers in excess of 10 fibers, longer than 5 micrometers, per cubic centimeter of air, as determined by the method just noted."

EFFECTS OF EXPOSURE: CAUTION: Breathing asbestos may cause serious bodily harm.

EMERGENCY AND FIRST AID PROCEDURES: No acute toxicity. Use respirator if airborne asbestos fiber concentration exceeds OSHA limits.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Avoid inhalation of dust. Remove spilled material by vacuum cleaner or by water wash.

WASTE DISPOSAL:

Bags and waste and scrap materials should be disposed of in a manner which will avoid airborne concentrations of asbestos, such as the use of dust-tight trash bags or containers. Ensure that disposal complies with all applicable federal, state or local regulations.

Union Carbide Corporation assumes no responsibility and makes no warranty, expressed or implied, repre- ...ment as to completeness, ...vided.

548

Published by AsbestosClaims.Law

asbestosclaims.law/library/19689/2

To: Executive Director
Asbestos Information Association/North America
1745 Jefferson Davis Hwy.
Crystal Square 4, Suite 509
Arlington, VA 22202


(Date)

Please forward the information materials noted below. We understand that we will be billed for costs plus shipping charges:



"What You Should Know About Asbestos and Health." Employee information pamphlet. 5"x7" 15¢ each.

Quantity_____




"Recommended Practices for Handling Asbestos Fiber." Heavy coated stock poster, 11"x14" printed blue on white for employee information boards. 25¢ each.

Quantity_____

Also available in 8½"x9" pamphlet form suitable for mailing in #10 envelope. 10¢ each.

Quantity_____



Booklets—Recommended Work Practices—$1.35 each

"Fabrication and Use of Asbestos Paper Products"

Quantity_____

"Shop and Field Fabrication of Asbestos Sheet Products"

Quantity_____

"Molding and Fabrication of Asbestos Containing Plastic Products"

Quantity_____

"Fabrication and Use of Asbestos Friction Materials"

Quantity_____

"Use and Handling of Asbestos Textile Products"

Quantity_____

Union Carbide trial exhibit UC-5206: R. E. Byrne, Jr. to Calidria Asbestos Customers Enclosing Material Safety Dat... Published by AsbestosClaims.Law
ACL Doc 19689 · Page 3 of 10 asbestosclaims.law/library/19689/3

Recommended Practices for

Handling Asbestos Fiber

'rotection from fire, absorption of heat from friction, ıigh tensile strength as a reinforcing material, resis- ance to corrosion and insulation from heat, cold and ıoise are among the properties of asbestos that esult in its use in hundreds of industrial applications nd home products.

ısbestos is the name given to a group of hydrated ilicate minerals that are characterized by fibrous rystallization. Though asbestos is fairly common to ne earth's crust, not all deposits are of commercial alue. Because asbestos is fibrous and, in a certain ange of sizes, can enter the lungs, maximum care hould be taken to avoid exposure to asbestos dust nd the hazards to health that can result.

ENERAL PRECAUTIONS

ı all stages of handling — packaging, transporting, ınloading, storing, and in-part moving —asbestos iber bags should be handled carefully and in such a ıanner as to prevent damage of bags and the ıeneration of dust.

)amaged bags should be immediately repaired, re- ealed or put into closed receptacles. Any spillage of sbestos fiber should be cleaned up immediately — ither by vacuum equipment or, after thoroughly vetting, by sweeping — and should be deposited in uitable closed receptacles.

onsult and observe OSHA regulations governing sbestos in the workplace; EPA rules on discharge o the ambient air; and other local codes, rules or egulations controlling the handling and use of sbestos fiber.

UNLOADING

Unitized loads should be lifted intact to and from holds of ships, and off and on land transport by forklift trucks or other suitable handling equipment.

Care should be taken to avoid puncturing the asbestos fiber bags during unloading from ships, rail- road cars, trucks or other modes of transportation. Hooks or other sharp instruments should not be used. Loose fiber accumulated during transit should be picked up by vacuum cleaner before unloading.

STORAGE

For storage, fiber bags should be stacked and moved with care to avoid breakage; protected from puncture by moving vehicles; and, if possible, should be isolated from traffic in the warehouse and covered to prevent dust generation. To prevent deterioration of stored bags, the principle of first-in, first-out should be followed.

HANDLING

Maximum possible enclosure and fully effective dust control systems should be provided at all stages of in-plant handling where dust is created, such as in bag opening, fiber dumping and bag disposal oper- ations. Loose fiber should be cleaned from work areas by vacuum cleaner, or after thoroughly wetting, by sweeping, and then deposited in covered recep- tacles.

PROTECTIVE EQUIPMENT

Wearing of respiratory equipment approved for pro- tection against asbestos dust should be required at all stages of asbestos fiber handling where quantities of dust are generated which cannot be kept within the permissible exposure limits by dust control equip- ment or other methods.

TRANSPORT

Where the use of asbestos requires the transport of loose fiber in open carts or buggies, covers should be used to prevent spilling and dust generation.

WASTE MATERIALS


Waste materials, such as collected dust and empty fiber bags, should be placed in special closed receptacles and disposed of in such a manner as to prevent the release of dust. Safety practices outlined above in the *HANDLING* and *PROTECTIVE EQUIP- MENT* sections should be followed during these operations.

All dust from exhaust systems should be collected and safely disposed of, being careful not to release dust into the outside air. Particular attention should be paid to the protection of employees whose job it is to dispose of collected dust from fabric filter dust collection and similar cleaning operations.

Union Carbide trial exhibit UC-5206: R. E. Byrne, Jr. to Calidria Asbestos Customers Enclosing Material Safety Dat... Published by AsbestosClaims.Law
ACL Doc 19689 · Page 4 of 10 asbestosclaims.law/library/19689/4

What You Should Know About Asbestos And Health

554



AIA
NORTH AMERICA

ASBESTOS INFORMATION ASSOCIATION
1660 L Street, N.W., Washington, D.C. 20036

Litho in U.S.A.


Union Carbide trial exhibit UC-5206: R. E. Byrne, Jr. to Calidria Asbestos Customers Enclosing Material Safety Dat...
ACL Doc 19689 - Page 5 of 10
Published by AsbestosClaims.Law
asbestosclaims.law/library/19689/5

Frankly Speaking

You certainly are important to your family and loved ones, and you are important to the company. It makes good sense for the company to do everything possible to protect you in your working environment, and for you to take every precaution to avoid possible hazards to your health.

If your work involves the use of asbestos or asbestos-containing products, you should be aware of:

- What the health hazards can be.
- What obligations your employer has to protect you.
- What you can do as an individual to protect your own health and that of your fellow employees.




These are the Facts

Exposure to asbestos fiber can increase the risk of developing certain diseases over a period of years. The four diseases associated with inhalation of asbestos fiber are: asbestosis — a non-malignant scarring lung condition; cancer of the lung, and to a lesser degree, cancer of the digestive tract; and mesothelioma — a rare cancer of the lining of the chest or abdominal cavities.

Reduction of asbestos dust exposure is at present the only known method of preventing disease among asbestos industry workers. Experience has shown that when dust levels are low, the risk to the worker and the incidence of asbestos-related disease is low.

Now . . . About Smoking

It has been established that cigarette smoking greatly increases the risk of developing lung cancer in persons exposed to asbestos. On the other hand, asbestos industry workers who do not smoke cigarettes — and who never have smoked regularly — have shown no greater frequency of lung cancer than the average person who does not smoke.




555

Union Carbide trial exhibit UC-5206: R. E. Byrne, Jr. to Calidria Asbestos Customers Enclosing Material Safety Dat...
ACL Doc 19689 - Page 6 of 10

Published by AsbestosClaims.Law
asbestosclaims.law/library/19689/6

If You Work in a Plant or Mine

Employees in asbestos mines, mills, or product manufacturing plants will be exposed to airborne asbestos fiber. But, when dust levels in mines, mills and factories are properly controlled, the asbestos content of the air will be low and within safe levels, and will not be a hazard to workers.



If You Work in Field Operations

Most finished asbestos-containing products, when correctly used, will not produce dust levels high enough to be a hazard to workers. In more than 90% of the asbestos-containing products made in the United States, the asbestos fibers are "locked in" the product by means of cement, plastic or other binders. Consequently, the fibers are not easily released into the air, except during sawing or certain other machining operations. The tear-out, removal or demolition of old asbestos-containing insulations also can release fibers. Such operations must be carried out with approved methods of dust suppression and control.



556

Union Carbide trial exhibit UC-5206: R. E. Byrne, Jr. to Calidria Asbestos Customers Enclosing Material Safety Dat...
ACL Doc 19689 - Page 7 of 10
Published by AsbestosClaims.Law
asbestosclaims.law/library/19689/7

Regulations to Protect You

To insure the safety of all, occupational standards for exposure to asbestos dust have been established by the Occupational Safety and Health Administration (OSHA) of the U.S. Department of Labor. These standards are designed to protect you from exposure to potentially hazardous amounts of asbestos dust and are being carefully observed by the company.

Here is what these standards provide:

1 A SAFE WORKPLACE

Your employer is required to make sure that no employee is exposed to more asbestos dust than permitted by the government standard. Your company will exert every effort to keep levels not only below permissible limits, but as low as possible.

2 IN CASE OF RISK

If exposure limits are exceeded, the employee will be notified by his employer, and will be informed of the corrective measures being undertaken to reduce his exposure to permitted levels.

3 CORRECTIVE ACTION

Engineering controls and safe work practices will be the approved methods of correction.



4 IN THE MEANTIME

While corrective measures are being taken, the employee will be protected by other means, which may include the wearing of an approved respirator provided by his employer, or by shift rotation.

5 TEMPORARY MEASURES

The use of respirators or shift rotation to achieve proper dust control will be permitted only (a) during the time necessary to install engineering controls or to institute safe work practices, (b) in situations where such controls or practices are not technically feasible, or (c) in emergencies.

6 AND ONLY IF YOU PASS THE MEDICAL

No employee will be assigned to a task requiring the use of a respirator if his most recent yearly medical examination indicates that he would not be able to function properly while wearing one, or if the wearing of the respirator would create a hazard to the employee's health or safety.

7 SPECIAL PROTECTION WHEN NEEDED

Protective clothing, change rooms, and separate clothes lockers will be provided for employees in situations where exposure standards are exceeded.



537

Union Carbide trial exhibit UC-5206: R. E. Byrne, Jr. to Calidria Asbestos Customers Enclosing Material Safety Dat...
ACL Doc 19689 - Page 8 of 10
Published by AsbestosClaims.Law
asbestosclaims.law/library/19689/8

8 CHECKING THE AIR

Monitoring of workplace air will be conducted by the employer to assure that government standards are being met. Employees may review results of the monitoring in their particular job areas.

9 SIGNS TO GUIDE YOU

Caution signs will be posted in work areas where airborne levels of asbestos may be in excess of the exposure limits, and where respiratory protection and special handling precautions are required. Employees should obey these signs at all times.

10 CAUTIONS ON PRODUCTS, TOO


Caution labels will be placed on asbestos-containing products which, during any reasonably foreseeable use, handling, application, machining or disposal may release asbestos fiber into the air in concentrations that exceed the exposure limits.

11 ANNUAL CHECK-UPS

The employer, at no cost to the employee, will provide yearly medical examinations for employees exposed to asbestos dust. Pre-employment and termination medical exams also are provided.

12 COUNSELING AND RESULTS AVAILABLE

Results of each employee's medical examination will be reviewed with him by a physician, and, at the worker's request, his own medical exam records will be made available to his family physician.



And, Most Important . . .

Another word about smoking. First, an assurance. If you don't smoke cigarettes now and never have smoked them regularly, statistical studies show you have no greater chance of getting lung cancer than a nonsmoker who has never worked with asbestos.

But, on the advice of medical specialists: If you work with asbestos and you do smoke cigarettes, **quit smoking!** If you work with asbestos and do not smoke, **don't start!**

Your family and the company need you and your special abilities. Guard your health in every way, but particularly where cigarette smoking is concerned.

After You Leave Work

You also should take precautions to prevent taking asbestos home on any work clothes or other materials in order to protect members of your family from possible exposure to asbestos dust.

To reduce the possibility of carrying asbestos fibers home on your person and clothing, facilities for showering and changing from work to regular clothes may be provided by your employer. Work clothing taken home for laundering should be carried in a closed bag or container and then washed separately from other family clothing.

Never take loose fiber home. Your family should not be needlessly exposed to asbestos dust through any carelessness on your part.



538


Published by AsbestosClaims.Law
asbestosclaims.law/library/19689/9

Union Carbide trial exhibit UC-5206: R. E. Byrne, Jr. to Calidria Asbestos Customers Enclosing Material Safety Dat...
ACL Doc 19689 - Page 9 of 10

What Else Can You Do?

Industrial safety and health can never be the responsibility of only one person. Both you and your employer must work together to provide a safe and healthy environment.

- For safety in specialized areas, detailed work practices must be instituted to make sure we are complying with government regulations. As an employee, it is your duty to follow these work practices at all times. Never take shortcuts that may endanger your health and that of others.
- If you see a possible hazard that your employer may have overlooked, bring it to his attention.
- If you can suggest more efficient and safer work practices, do so. If you are not sure how to handle a material or perform an operation without creating dust, talk with your supervisor first.



REMEMBER

539

- Asbestos fiber may be hazardous to your health, and exposure to it, over a period of time, may increase your risk of developing asbestosis, cancer of the lung or digestive tract, or mesothelioma.
- Every precaution should be taken by you and your employer to keep dust levels low and to avoid unnecessary exposure.
- The asbestos industry is working hard to control dust exposure and to alert every worker to proper safety precautions. Government and company regulations designed to protect you and other workers against exposure to asbestos dust should be strictly followed by everyone.
- The vast majority of the thousands of finished asbestos products are not hazardous when properly handled or used, but workers who are engaged in their manufacture, fabrication or installation should be aware of possible dangers. Don't be careless — urge your fellow workers not to be.
- Asbestos is used in some 3,000 products daily throughout the world . . . products that help prevent and control fire in our homes, schools, factories, offices, hospitals and theaters . . . products that help stop our cars and trucks . . . products that save fuel and energy in this important time of conservation. If we are to continue making these much-needed products, it is important that you and your employer cooperate in maintaining the highest standards of safety and health on the job.

Union Carbide trial exhibit UC-5206: R. E. Byrne, Jr. to Calidria Asbestos Customers Enclosing Material Safety Da...
ACL Doc 19689 - Page 10 of 10
Published by AsbestosClaims.Law
asbestosclaims.law/library/19689/10